Product ID:Q-MAX A27 MSDS Date:01/01/1991

FSC:8010

NIIN:00-807-7497

MSDS Number: BPRKD === Responsible Party ===

Company Name: MAVIDON CORPORATION Address: 3953 SW BRUNER TERRACE

City:PALM CITY

State:FL ZIP:34990 Country:US

Info Phone Num:407-286-8951

Emergency Phone Num:407-286-8951 OR 800-535-5053

CAGE:MO005

==

Contractor Identification ===Company Name:MAVIDON CORPAddress:3953 BRUNER TERRACE

Box:City:PALM CITY

State:FL ZIP:34990 Country:US

Phone:407-286-8951

CAGE:0EUM3

Company Name: MAVIDON CORPORATION Address: 3953 SW BRUNER TERRACE

Box:City:PALM CITY

State:FL ZIP:34990 Country:US

Phone: 407-286-8951

CAGE:MO005

======= Composition/Information on Ingredients ========

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Other REC Limits: NONE SPECIFIED

OSHA PE

L:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

========== Hazards Identification ===========================

LD50 LC50 Mixture: NOT KNOWN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED CONTACT WITH SKIN WILL DRY AND DEFAT THE SKIN,LEADING TO DERMATITIS.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANEN

T BRAIN AND NERVOUS SYST EM DAMAGE.INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENT MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN:CONTACT MAY CAUSE IRRITATION.INHALATION:EFFECTS OF HIGH VAPOR CONCENTRATIONS MAY RANGE FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure: NOT KNOWN

First Aid:EYES:FLUSH WITH LARGE AMOU NTS OF WATER FOR AT LEAST 15

MINUTES . SKIN:REMOVE CONTAMINATED CLOTHING, WASH SKIN WITH SOAP AND WARM WATER. INGESTION:DO NOT INDUCE VOMITING.CALL PHYSICIAN. INHALATION :REMOVE FROM EXPOSURE IMMEDIATELY.CALL PHYSICIAN.IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION, ADMINISTER OXYGEN.

Flash Point Method:TCC Flash Point:75F,23C Lower Limits:1% Upper Limits:7%

Extinguishing Media: CARBON DIOXIDE, DRY C

HEMICAL, OR REGULAR FOAM. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) AND FULL TURNOUT GEAR .COOL EXPOSED CONTAINERS WITH WATER SPRAY, AVOID BREATHING VAPOR OR FUMES. Unusual Fire/Explosion Hazard: DO NOT MIX WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN. ======== Accidental Release Measures ============ Spill Release Procedures: ELIMINATE IGNITION SOURCES, KEEP PEOPLE AWAY, RECOVER FREE LIQUID, ADD ABSORBENT (SAND, EARTH .SAWDUST).AVOID BREATHING VAPORS. VENTILATE CONFINED SPACES. ALERT AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTE R SEWERS, WATERCOURSES OR EXTENSIVE LANDAREAS. Neutralizing Agent:NOT KNOWN ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.ADEQUATE VENTILATION IS REQUIRED. Other Precautions: NOT KNOWN ========= Exposure Controls/Personal Protection ======= Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED. Ventilation:LOCAL EXHAUST:FACE VELOCITY >60 FPM. Protective Gloves: CHEMICAL RESISTANT GLOVES. Eye Protection: CHEMICAL SPLASH GOGGLES. Other Protective Equipment: SUFFICIENT CLOTHING TO PREVENT CONTACT WITH SKIN (CHEMICAL RESISTANT APRON). WASH CONTAMINATED SKIN WITH SOAP AND WATER. Work Hygienic Pract ices:AVOID BREATHING VAPORS, PROLONGED OR REPEATED CONTACT.REMOVE CONTAMINATED CLOTHING & SHOES, DRY SHOES BEFORE REUSE. Supplemental Safety and Health VAPOR PRESSURE:25 MMHG AT 77F,25C. ========= Physical/Chemical Properties ===========

Boiling Pt:B.P. Text:290F,143C

Vapor Pres:SUP DATA Vapor Density:3.7(AIR=1) Spec Gravity:0.87 (WATER=1)

Solubil

Melt/Freeze Pt:M.P/F.P Text:90F,32C

Decomp Temp:Decomp Text:NOT KNOWN

Evaporation Rate & Reference: 0.7 (BUTYL ACETATE=1)

ity in Water:NEGLIGIBLE
Appearance and Odor:WATER WHITE TO AMBER LIQUID WITH AROMATIC
HYDROCARBON ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NONE ESTABLISHED
Hazardous Decomposition Products:FUMES,SMOKE AND CARBON MONOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOS
AL MUST BE IN ACCORDANCE WITH
FEDERAL,STATE,AND LOCAL REGULATIONS.COORDINATE WITH SUPPORTING
INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.