View NSN Online: https://aerobasegroup.com/nsn/8010-00-935-7079 PLASTI-KOTE COMPANY, INC. -- AEROSOL SPRAY PAINT, BLACK 37038 -- 8010-00-935-7079 Product ID:AEROSOL SPRAY PAINT, BLACK 37038 MSDS Date:01/31/1990 FSC:8010 NIIN:00-935-7079 MSDS Number: BPRLV === Responsible Party === Company Name: PLASTI-KOTE COMPANY, INC. Address:1000 LAKE RD. City:MEDINA State:OH ZIP:44256 Country:US Info Phone Num:216-725-4511 **Emergency Phone** Num:216-725-4511 CAGE:DO534 === Contractor Identification === Company Name: PLASTI-KOTE COMPANY, INC Address:1000 LAKE RD City:MEDINA State:OH ZIP:44256 Phone:216-725-1511 CAGE:DO534 Company Name: TEMPO PRODUCTS CO A PLASTI-KOTE CO INC Address:1000 LAKE ROAD Box:City:MEDINA State:OH ZIP:44256 Country:US Phone:330-725-4511 CAGE:07708 ======= Composition/Information on Ingredients ========

Ingred Name: NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

====== Fire Fighting

Measures	=======================================
Floob Doint	·ND

Flash Point:NR Lower Limits:1.0

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WATER INEFFECTIVE, USE (FOG NOZZLE PREFERRED)
TO COOL CNTNRS TO PREVENT PRESSR BLDUP/AUTOIGNIT/EXPLOS W/HEAT. USE
SCBA W/FULL FACEPIECE IN POSITIVE PRESSR MODE.

Unusual Fire/Explosion Hazard:CLSD CNTR MAY EXPLODE/AUTOIGNIT W/HEAT.

VAPOR HEAVIER THAN AIR, TRAVEL ALONG GROUND/MOVED BY VENT & IGNITED BY IGNIT SOURCE AT LOCATION DISTANCE FROM

HANDLING.

===== Exposure Controls/Personal Protection ========

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:V3

Boiling Pt:B.P. Text:104 TO 331F

Melt/Freeze Pt:M.P/F.P Text:EST 1500F

Vapor Pres:SEE INGRED Vapor Density:> AIR

Spec Gravity: