

R.H.CARLSON COMPANY,INC. -- NORSIL SILICONE PRIMER -- 8040-00-938-1535

=====  
Product Identification  
=====

Product ID:NORSIL SILICONE PRIMER

MSDS Date:02/04/1994

FSC:8040

NIIN:00-938-1535

Kit Part:Y

MSDS Number: BPRLZ

=== Responsible Party ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Info Phone Num:203-531-5500

Emer

gency Phone Num:203-531-5500

CAGE:33530

=== Contractor Identification ===

Company Name:CARLSON R H CO- NORTHERN LABS DIV

Address:41 CHESTNUT ST

Box:City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500(73)FAX -0032 (JACKIE)

CAGE:2L329

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGREDIENT

FOR THIS FORMULATION\_INGREDIENT

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:WARNING! MAY CAUSE IRRITATION. AVOID CONTACT WITH SKIN,EYES & CLOTHING. CONTACT WITH UNCURED PRODUCT OR ITS VAPORS MAY CAUSE IRRITATION, DERMATITIS. INHALATION OF THE VAPORS MAY PRODUCE RESPIRATORY IRRITATION,DIZZINESS,HEADACHE,NAUSEA,MENTAL CONFUSION. INGESTION MAY BE HARMFUL & PRODUCE ABDOMINAL PAIN & DIARRHEA.  
Explanation of Carcinogenicity:MFR LISTED NO INFORMATION ABOUT THE CARCINOGENICITY OF THIS MATERIAL. HMIS DOES NOT EXPECT IT TO BE CARCINOGENIC.  
Effects of Overexposure:EYE/SKIN CONTACT WITH UNCURED PRODUCT OR ITS VAPORS MAY CAUSE IRRITATION, DERMATITIS. INHALATION OF THE VAPORS MAY PRODUCE RESPIRATORY IRRITATION,DIZZINESS,HEADACHE,NAUSEA,MENTAL CONFUSION. INGESTION MAY BE HARMFUL & PRODUCE ABDOMINAL PAIN& DIARRHEA.  
Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN BY MFR ON MSDS.

=====  
===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR. EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. AID/RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER TO DILUTE & GET IMMEDIATE MEDICAL CARE. NOTHING BY MOUTH IF UNCONSCIOUS.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:-4F,-20C  
Lower Limits:1.1  
Upper Limits:7.5  
Extinguishing Media:USE FOAM, CO2 OR DRY CHEMICALS. USE STANDARD FIREFIGHTING TECHNIQUES.  
Fire Fighting Procedures:PREVENT HUMAN EXPOSURE TO FIRE,SMOKE,FUMES OR PRODUCTS OF COMBUSTION. EVACUATE NON-ESSENTIAL PERSONNEL. WEAR FULL-FACE SCBA & IMPER

VIOSU PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. AVOID SPARKS,FIRE,HOT METAL SURFACES. HIGHLY FLAMMABLE DUE TO SOLVENT. VAPORS FORM EXPLOSIVE MIXTURES WITH AIR.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECT CLOTH/SPLASH GOGGLES. SOAK UP LIQ W/ABSORB (SAWDUST-CLAY-OIL ABSORB). SWEEP UP ABSORB MATL-PLACE IN CHEM WASTE DRUM FOR DISPOSAL. WASH AREA W/DETERGENT AND WATER,  
FLUSH W/WATER. LG SPILLS -DIKE AND PUMP INTO DRUM FOR SALVAGE ORDISPOSAL.

Neutralizing Agent:NO INFORMATION GIVEN BY MFR ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT W/SKIN&EYES. USE ONLY IN A WELL VENT AREA, KEEP AWAY FROM HEAT SOURCES & TIGHTLY CLOSED WHEN NOT IN USE. DO NOR LAY CNTNRS ON THEIR SIDE

Other Precautions:CONTACT LENS WEARERS TAKE APPROPRIATE PRECAUTION. USE NON SPARKING TOOLS

WHEN CLEANING UP SPILLS. SAFETY SHOWERS AND EYE BATH STATIONS SHOULD BE AVAILABLE. STATIC ELECTRICITY MAY ACCUMULATE AND CAUSE A FIRE HAZARD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:HANDLE IN OPEN, WELL VENTILATED AREA. WHERE ADEQUATE VENT IS NOT AVAILABLE, USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. WHERE EXPOSURE NECCESITATES A HIGHER LEVEL OF PROTECTION,USE A POSITIVE PRESSUR E AIR SUPPLIED RESPIRATOR.

Ventilation:LOCA

L EXHAUST IS REQUIRED AND GENERAL MECHANICAL VENTILATION IS SUGGESTED IN A CLOSED AREA.

Protective Gloves:PLASTIC FILM OR RUBBER.

Eye Protection:PROTECTIVE GOGGLES OR GLASSES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER

Work Hygienic Practices:KEEP AWAY FROM HEAT, SPARKS AND FLAME. AVOID PROLONGED VAPOR BREATHING AND CONTACT WITH SKIN AND EYES.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic

Num:NONE

Boiling Pt:B.P. Text:156F,69C

Vapor Pres: 1

Solubility in Water:NOT SOLUBLE

Appearance and Odor:COLORLESS, TRANSPARENT LIQUID WITH SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

WATER, ACIDS AND ALKALIS.

Stability Condition to Avoid:ACTIVE INGREDIENTS REACT WITH WATER, ACIDS  
AND ALKALIS, BUT DO NOT PRESENT A HAZARD.

Hazardous Decomposition Products:METHANOL (FLAMMABLE/POISONOUS LIQUID)  
AND 2-PROPANOL

(FLAMMABLE/LIQUID)

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:MATERIAL THAT CANNOT BE USED SHOULD BE DISPOSED  
OF IN AN EPA AUTHORIZED FACILITY. DISPOSE OF EMPTY CONTAINERS  
ACCORDING TO ANY APPLICABLE REGULATIONS UNDER THE RESOURCE  
CONSERVATION AND RECOVERY ACT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements

of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.