View NSN Online: https://aerobasegroup.ae/nsn/2530-01-290-4471

Product ID:C 175, ASBESTOS MSDS Date:10/22/1988 FSC:2530 NIIN:01-290-4471 **MSDS Number: BPRQX** === Responsible Party === Company Name: FORD MOTOR COMPANY Address:3000 SCHAEFER ROAD Box:1902 **City:DEARBORN** State:MI ZIP:48121 Country:US Info Phone Num:313-337-3182 OR 313-323-0045 Emergency Phone Num:313-337-3182 С AGE:2J502 === Contractor Identification === Company Name: FORD MOTOR CO, GOVERNMENT PART SALES Address:3000 SCHAEFER ROAD Box:1902 City:DEARBORN State:MI ZIP:48121 Country:US Phone:313-323-0045 CAGE:23040 Company Name: FORD MOTOR COMPANY Address:3000 SCHAEFER ROAD Box:1902 City:DEARBORN State:MI ZIP:48121 Country:US Phone:800-959-3673 CAGE:2J502 Ingred Name: ASBESTOS (FRIABLE) (SARA III) CAS:1332-21-4

RTECS #:CI6425000

Fraction

by Wt: > 60% Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE 1910.1001 ACGIH TLV:0.2 - 2 FIBERS/CC EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE & CHRONIC-HARMFUL IF INHALED/SWALLOWED.MAY CAUSE IRRITATION OF EYES, SKIN & RESPIRATORY TRACT.PROLONGED/REPEATED BREATHING OF ASBESTOS PA **RTICLES CAN** PRODUCE CHRONIC LUNG DISEASE(ASBESTOSIS), PLEUR AL PLAQUE & CANCER.SYMPTOMS MAY TAKE YEARS TO DEVELOP.SMOKERS ARE AT A GREATER RISK OF DEVELOPING CANCER FROM ASBESTOS. Explanation of Carcinogenicity: ASBESTOS IS REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: HARMFUL IF INHALED/SWALLOWED. MAY CAUSE **IRRITATION OF EYES, SKIN & RESPIRATORY TRACT. PROLONGED/REPEATED** BREATHING OF ASBESTOS PARTICLES CAN PRODUCE CHRONIC LUNG DISEASE (ASBESTOSIS), PLEURAL PLAQUE & CANCER. SYMPTOMS MAY TAKE YEARS TO DEVELOP. SMOKERS ARE AT A GREATER RISK OF DEVELOPING CANCER FROM ASBESTOS. Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING RESPIRATORY SYSTEMS DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT. First Aid:SEEK MEDICAL ATTENTION IF SYMPTOMS DEVELOP. EYES:GENTLY RINSE WITH WATER FOR 15 MINUTES WHILE KEEPING EYELIDS OPEN. SKIN:WASH FREQUENTLY WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR.

INGESTION: GET IMMEDIATE MEDICAL ATTENTION OR ADVICE.

Flash Point:NON FLAMMABLE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OPERATED IN THE POSITIVE PRESSURE MODE T O PREVENT INHALATION OF FIBERS. Unusual Fire/Explosion Hazard:ASBESTOS FIBERS MAY BECOME AIRBORNE DURING FIRE FIGHTING ACTIVITIES.

Spill Release Procedures:TREAT DUST AS FREE ASBESTOS. DO NOT DRY SWEEP OR USE COMPRESSED AIR. WET METHOD SHOULD BE USED FOR EXTRACTION OF DUST AND DEBRIS. HIGH EFFICIENCY PARTICULATE APPARATUS (HEPA) VACUUMS SHOULD BE USED. D O NOT ALLOW THIS MATERIAL TO ENTER SEWERS ETC...

Neut

ralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions:STORAGE- DO NOT STIR UP THE DUST. THIS PRODUCT FOR USE BY QUALIFIED PERSONNEL ONLY.

Other Precautions: USE IN WELL VENTILATED AREA. AVOID BREATHING DUST OR FIBERS. MINIMIZE CONTACT WITH SKIN. AVOID CONTACT WITH EYES. DO NOT RAISE DUST. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP AWAY FROM REACH OF CHILDREN.

====== Ex

posure Controls/Personal Protection ========

Respiratory Protection:USE NIOSH APPROVED HIGH EFFICIENCY FIBERS/FUMES RESPIRATOR WHEN AIRBORNE FIBER CONCENTRATIONS EXCEED THE PEL. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. CHECK LOCAL REGULATIONS FOR EMISSION STANDARDS. Protective Gloves:LEATHER, COTTON OR RUBBER AS NEEDED Eye Protection:DUST-RESISTANT SAFETY GOGGLES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED. DO NOT WE AR CONTACT LENSES Work Hygienic Practices:DON'T TAKE PROTECTIVE GEAR/CLOTHING HOME IF EXPOSED TO DUST. DON'T SHAKE. DON'T EAT IN AREA WHERE ASBESTOS/DUST PRESENT.

Supplemental Safety and Health

HCC:T7 Spec Gravity:3.350 Appearance and Odor:WHITE SOLID

Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:FIRE, EXTREME H

EAT Hazardous Decomposition Products:NONE KNOWN

Waste Disposal Methods:WASTE SHOULD BE CONTAINED IN IMPERMEABLE BAGS, LABELED AND DISPOSED IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. REPORTABLE QUANTITY FOR ASBESTOS IS 1 POUND.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.