

MOBIL OIL CORP -- MOBIL 1 SYNTHETIC GEAR LUBRICANT -- 9150-01-363-1192

===== Product Identification =====

Product ID:MOBIL 1 SYNTHETIC GEAR LUBRICANT

MSDS Date:12/30/1992

FSC:9150

NIIN:01-363-1192

MSDS Number: BPRRX

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-227-0707 X3265 S. CASTILLO

Emergency P

hone Num:609-737-4411/CHEMTREC 800-424-9300

CAGE:6G112

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ

ZIP:08540

Country:US

Phone:609-737-4411

CAGE:6A687

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525, 856-224-4644

CAGE:6G112

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Compositi

on/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS (INERT)

Fraction by Wt: >85%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: SLIGHT IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:SLIGHT SKIN IRRITATION.  
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:EYES- FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS,  
CALL A PHYSICIAN. SKIN- WASH CONTACT AREAS WITH SOAP AND WATER.  
INHALATION AND INGESTION: NOT EXPECTED TO BE A PROBLEM.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>325F,>163C  
Lower Limits:0.6%  
Upper Limits:7.0%  
Extinguishing Media:CO2, FOAM, DRY CHEMICAL & WATER FOG.  
Fire Fighting Procedures:WATER AND FOAM MAY CAUSE FROTHING.  
FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:USE WATER TO KEEP FIRE EXPOSED CONTAINERS  
COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

===== Accidental Release Measures =====

Spill Release Procedures:ADSORB ON FIRE RETARDANT TREATED SAWDUST,  
DIATOMACEOUS EARTH, ETC. SHOVEL UP & SAVE IN A CONTAINER FOR  
DISPOSAL.

===== Ha

Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

Other Precautions:UNUSED PRODUCT IS NOT A HAZARDOUS WASTE. USED PRODUCT  
MAY BE REGULATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY  
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE  
AND WITH ADEQUATE VENTILATION.

Protect

ive Gloves:NO SPECIAL EQUIPMENT REQUIRED

Eye Protection:NO SPECIAL EQUIPMENT REQUIRED

Other Protective Equipment:EYE WASH.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS  
BE FOLLOWED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: