View NSN Online: https://aerobasegroup.com/nsn/8040-00-539-7798

Product ID:EPIBOND 1217 B MSDS Date:01/27/1989 FSC:8040 NIIN:00-539-7798 Kit Part:Y MSDS Number: BPVBH === Responsible Party === Company Name: CIBA-GEIGY CORPORATION, FURANE PRODUCTS DIVISION Address:5121 SAN FERNANDO RD WEST **City:LOS ANGELES** State:CA ZIP:90039-1011 Country:US Info Phone Num:818-247-6210, 800-334-9481 Emergency Phone Num:818-247-6210, 800-334-9481 CAGE:99384 === Contractor Identification === Company Name: CIBA SPECIALTY CHEMICALS CORP, N. A. / PERFORMANCE POLYMERS Address:5121 SAN FERNANDO RD WEST Box:City:LOS ANGELES State:CA ZIP:90039-1011 Country:US Phone:818-247-6210/800-873-1138 CAGE:99384 Ingred Name: MERCAPTAN POLYMER Fraction by Wt: 85% Other REC Limits:NONE SPECIFIED In gred Name:2,4,6-TRIS(DIMETHYLAMINOMETHYL) PHENOL CAS:90-72-2 RTECS #:SN3500000 Fraction by Wt: 5% Other REC Limits: FCP: 5 PPM Ingred Name:SILICA CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 10% Other REC Limits: FPC: 10 MG/M3 OSHA PEL:80 MG/M3 ACGIH TLV:10 MG/M3 

Effects of Overexposure:INHALE: VAPOR/MIST IRRITATE NOSE/THROAT. EYE: SEVERELY IRRITATING/POSSIBLE PERMANENT INJURY. SKIN: SEVERELY IRRITATING/HARMFUL IF

ABSORBED. INGEST: BURNING/SEVERE SWELLING OF
MOUTH/THROAT/ABDOMEN. DEL AYED EFFECTS: PROLONGED/REPEATED
EXPOSURE: ALLERGIC REACTION.
Madical Cond Assuremented by Europeuron ALLERCY ECZEMA EVE OD DECDIDATOD

Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA, EYE OR RESPIRATORY CONDITIONS.

First Aid:INHALE: MOVE TO FRESH AIR. EYE: FLUSH W/WATER 15 MIN. GET PROMPT MED ATTEN. SKIN: WASH W/SOAP/WATER. REMOVE/WASH CLOTHES BEFORE REUSE. INGEST: DILUTE W/2 GLASSES WATER. SEE PHYSICIA N.

NEVER GIVE ANYTH ING BY MOUTH TO UNCONSCIOUS PERSON. PHYSICIAN NOTE: ALLERGIC DERMATITIS/RESPIRATORY RESPONSE IN SUSCEPTIBLE INDIVIDUALS MAY BE DELAYED. IT MAY APPEAR AFTER WEEKS/MONTHS OF FREQUENT/PROLONGED CONTACT.

Flash Point Method:COC

Flash Point:>255F,>124C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY
Fire Fighting Procedures:WEAR BREATHING APPARATUS (MSHA/NIOSH-APPROVED,
PR

ESSURE DEMAND, SELF-CONTAINED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

Spill Release Procedures:USE PROTECTIVE EQUIPMENT. CLEAN ALL TRACES. SHOVEL MATERIAL AS POSSIBLE INTO DRY/CLEAN CONTAINER. HARD SURFACES: USE ABSORBENT MATERIAL-PICK UP REMAINDER, LOOSE SURFACES: SHOVEL UP CONTAMINATED LAYER. KEEP SPILLS/CLEANING RUNOFFS O UT OF

MUNICIPAL \*

 Handling and Storage Precautions:MAX TEMP: 35C. STORE AWAY FROM EXCESSIVE HEAT (EG: STEAMPIPES/RADIATORS)/SOURCES OF HEAT/REACTIVE MATERIALS. DO NOT STORE NEAR FOOD/FEED. CORROSIVE \*\*
Other Precautions:\*SEWERS/OPEN BODIES OF WATER. \*\*TO COPPER/BRASS ON LONG STORAGE.

Respiratory Protection:WEAR RESPIRATOR (MSHA/NIOSH-APPROVED

 ) SUITABLE FOR CONCENTRATIONS AND TYPE OF AIR CONTAMINANTS ENCOUNTERED.
Ventilation:MECHANICAL LOCAL EXHAUST VENTILATION AT POINT OF CONTAMINANT RELEASE.
Protective Gloves:IMPERVIOUS PLASTIC/RUBBER
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHING, SAFETY SHOWER AND EYEWASH FACILITY.
Supplemental Safety and Health
KEY1=F7. MSDS REPRESENTS PART B OF 2 PART KIT. SEE PNI C THIS NSN/CAGE FOR PART A.

======= Physical/Chemical Properties

\_\_\_\_\_

HCC:F8 Vapor Pres:1 (AIR=1) Spec Gravity:1.19 Viscosity:SOFT PASTE Evaporation Rate & amp; Reference: