

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- 322611-02611 CYLESSTIC TK 680 --
9150-01-348-3093

===== Product Identification =====

Product ID:322611-02611 CYLESSTIC TK 680

MSDS Date:06/01/1989

FSC:9150

NIIN:01-348-3093

MSDS Number: BPVLG

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Ph

one Num:713-656-5949 FAX: 713-656-3631

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

Company Name:SALATHE OIL CO

Box:UNKNOW

CAGE:NO789

=====
Composition/Information on Ingredients
=====

Ingred Name: DISTILLATES, HYDROTREATED HEAVY PARAFFINIC
CAS: 64742-54-7
RTECS #: PY8035500
Fraction by Wt: 85%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Ingred Name: ASPHALT (PETROLEUM)
CAS: 8052-42-4
RTECS #: CI9900000
Fraction by Wt: 500F
Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SEL
F CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
Accidental Release Measures
=====

Spill Release Procedures: CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL
TO ENTER SEWERS OR WATERCOURSES, REMOVE ALL SOURCES OF IGNITION.
ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC.

=====
=== Handling and Storage
=====

Handling and Storage Precautions: DO NOT TRANSFER TO UNMARKED
CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN
FLAME, OR OXIDIZING MATERIALS. COMBUSTIBLE LIQUID.
Other Precautions: MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.
LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF
CONTAMINATED LEATHER ARTICLES THAT CAN NOT BE DECONTAMINATED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: USE NIOSH/MSHA APPROVED AIR-PURIFYING RESPIRATOR
FOR ORGANIC VAPORS AND PARTICULATES OR AN ATMOSPHERE-SUPPLYING
RESPIRATOR IF REQUIRED. PROTECTION IS NOT REQUIRED UNDER NORMAL USE
CONDITIONS.
Ventilation: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE.
MECHANICAL EXHAUST RECOMMENDED IF USED IN ENCLOSED AREA.
Protective Gloves: CHEMICAL RESISTANT GLOVES (NITRILE BEST)
Eye Protection

ction:WEAR CHEMICAL SAFETY GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING, APRON AND BOOTS AS REQUIRED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DIRNKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311 OF THE CLEAN WATER ACT. SPILLS ENTERING SURFACE WATERS OR ANY WATER COURSES OR SEWERS ENTERING/LEADING TO SURFACE WATERS TH

AT CAUSE A SHEEN MUST

BE REPORTED TO THE NATIONAL RESPONSE CENTER. 800-424-8602

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:610F,321C

Melt/Freeze Pt:M.P/F.P Text:20.0F,-6.7C

Vapor Pres:6 (AIR=1)

Spec Gravity:0.92

Viscosity:627 CST @ 40C

Evaporation Rate & Reference: