

PRATT & LAMBERT, INC INDUSTRIAL COATINGS DIVISION -- LACQUER CAMOUFLAGE RED 11136  
ID 787101 -- 8010-00-166-3151

=====  
Product Identification  
=====

Product ID:LACQUER CAMOUFLAGE RED 11136 ID 787101

MSDS Date:08/11/1992

FSC:8010

NIIN:00-166-3151

MSDS Number: BQCNS

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC INDUSTRIAL COATINGS DIVISION

Box:2153

City:WICHITA

State:KS

ZIP:67201

Countr

y:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOBUTYL ACETATE (SARA III) (SOLVENT) (LFL 2.0, UFL 11.0)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/700 MG/M3

ACGIH TLV:150 PPM/700 MG/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III) (SOLVENT) (LFL 1.7, UFL 7.1) (VAPOR  
PRESSURE 22 MM HG @ 20C)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

VENT) (LFL 3.0, UFL 13.0)  
(VAPOR PRESSURE 33 MM HG @ 20C)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/STEL 500 PPM  
ACGIH TLV:400 PPM/STEL 500 PPM

Ingred Name:NITROCELLULOSE (RESIN)  
CAS:9004-70-0  
RTECS #:QW0970000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SARA III) (SOLVENT) (LFL 1.0, UFL 11.0)  
(VAPOR PRESSURE 10 MM HG @ 20C)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: 5%  
Other REC Limits:NON  
E SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE (PIGMENT) (SARA 313)  
CAS:7758-97-6  
RTECS #:GB2975000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:.05MG/M3/.1MG/M3CEIL  
ACGIH TLV:0.0120 MG/M3

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 5 MM HG @ 20 C) (LFL 1.0,  
UFL 7.0)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/STEL 150 PPM  
ACGIH TLV:100 PPM/STEL

150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE (PIGMENT)  
CAS:14464-46-1  
RTECS #:VV7325000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:SEE TABLE Z3  
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (PIGMENT)  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:2 MG/M3/ 20 MPPCF  
ACGIH TLV:2 MG/M3/ 15 MPPCF

Ingred Name:SILICA, CRYSTALLINE  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 200 C  
ST  
Evaporation Rate & Reference:SLOWER THAN DIETHYL EHTER  
Solubility in Water:SLIGHT IN WATER  
Appearance and Odor:LIQUID, SOLVENT ODOR  
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.  
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES  
OF IGNITION.  
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY  
WE  
LDING/ CUTTING: SMOKE, CO, CO2, OXIDES OF NITROGEN, CHROMIUM &  
LEAD MAY BE GENERATED

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE & LOCAL  
LAWS/REGS. INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERATE  
CLSD CNTNR. OBSERVE PRECAUTION FOR DISPOSAL OF FLAMM MAT'L. DISPOSE  
CONTAM ABSORB IN HZD WASTE L ANDFILL. D001. IF LEAD >5.0 MG/L,  
D008.EP TOXIC.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.