View NSN Online: https://aerobasegroup.ae/nsn/5330-00-969-8486

ARMSTRONG WORLD INDUSTRIES INC -- AN-890 ASBESTOS ACCOPAC -- 5330-00-969-8486

Product ID: AN-890 ASBESTOS ACCOPAC MSDS Date:08/15/1986 FSC:5330 NIIN:00-969-8486 **MSDS Number: BQCTT** === Responsible Party === Company Name: ARMSTRONG WORLD INDUSTRIES INC Address:W LIBERTY AND CHARLOTTE ST Box:3001 **City:LANCASTER** State:PA ZIP:17604 Country:US Info Phone Num:717-396-2729 Emergency Phone Num:717-396-2729 Preparer's Name: D. E. BOUDER CAGE:03938 === Contractor Identification === Company Name: AR BEE CORP Address:2455 AMERICAN LN Box:City:ELK GROVE VILLAGE State:IL ZIP:60007-6263 Country:US Phone:312-595-7334 CAGE:52993 Company Name: ARMSTRONG WORLD INDUSTRIES, INC. Address:313 W. LIBERTY ST. Box:3209 City:LANCASTER State:PA ZIP:17604 Country:US Phone:717-396-2328; 717-396-2935 CAGE:03938

Ingred

Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:SYNTHETIC RUBBER Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION. INGESTION- IRRITATION OF GI TRACT.

INHALATION-IRRITATION OF

RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, & MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER OF THE BOWEL.

Explanation of Carcinogenicity: THIS PRODUCT CONTAINS ASBESTOS [12001-29-5], AN OSHA REGULATED CARCINOGEN.

Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES: IRR

ITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS. DIARRHEA, VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SE E DOCTOR.

INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

Flash Point:NOT REQUIRED

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTAN T AND THEN SHOVEL OR MOP UP CONTAMINATION.

Handling and Storage Precautions: ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN

NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions: IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDE RAL REGULATIONS FOR ASBESTOS.

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQU

IRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN. Protective Gloves:COTTON OR LEATHER

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDER CONTAMINATED CLOTHING BEFOR E REUSE.

Supplemental Safety and Health AR BEE P/N: W7-3W21482.

HCC:T6

Solubility in Water:NEGLIGIBLE Appearance and Odor:FLEXIBLE SHEETING WITH A RUBBER ODOR Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS Stability Condition to Avoid:ACCUMULATIONS OF DUST Hazardous Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT. PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for

use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.