

SCHARPF GROUP, INC -- SG-50 (A,B) -- 8030-00-709-3327

===== Product Identification =====

Product ID:SG-50 (A,B)  
MSDS Date:02/19/1992  
FSC:8030  
NIIN:00-709-3327  
MSDS Number: BQDLN  
=== Responsible Party ===  
Company Name:SCHARPF GROUP, INC  
Address:3791 PICKETT ROAD  
City:OSHKOSH  
State:WI  
ZIP:54904  
Country:US  
Info Phone Num:414-233-7146  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer's Name:MIKE SCH  
ARPF  
CAGE:0NLJ2  
=== Contractor Identification ===  
Company Name:SCHARPF GROUP, INC  
Address:3791 PICKETT ROAD  
Box:City:OSHKOSH  
State:WI  
ZIP:54904  
Country:US  
Phone:414-233-7146  
CAGE:0NLJ2

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE (MINERAL SPIRITS)  
CAS:64742-47-8  
RTECS #:GA5504000  
Fraction by Wt: 46%  
Other REC Limits:\*AS STODDARD SOLVENT  
OSHA PEL:400 PPM/1600 MG/M3  
ACGIH TLV:100 PPM/525 MG/M3 \*

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE TOXICOLOGICAL PROPERTIES; FOR MINERAL SPIRITS: INHALATION - IRRITATION OF EYES, NOSE, THROAT, DIZZINESS. SKIN CONTACT - DERMATITIS. EYE CONTACT - IRRITATION. INGESTION - NAUSEA, VOMITING. LARGE AMOUNTS, IF RETAINED, LEAD TO SYMPTOMS OF CENTRAL NERVOUS SYSTEM DEPRESSION.

Effects of Overexposure:CHRONIC EFFECTS OF OVEREXPOSURE: MAY CAUSE EYE, NOSE AND THROAT IRRITATION AND DIZZINESS IF USED IN UNVENTILATED AREA.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER 15 MIN. IF IRRIT PERSISTS, CONTACT DR. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN W/SOAP & WATER. IF IRRITATION DEVELOPS, CONTACT DR. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIF RESPIRATION, PREFERABLE MOUTH TO MOUTH. IF BREATHING DIFFICULT, GIVE OXYGEN. CALL DR IMMED. INGESTION: DONT INDUCE VOMITING. CONTACT DR IMMEDIATELY. NOTHING BY MOUTH TO UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:106F,41C

Lower Limits:.8

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, CLOSED CONTAINERS EXPOSED TO FIRE MAY BE COOLED WITH WATER SPRAY.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED FOR FIREFIGHTERS. WATER SPRAY MAY BE USED WITH CAUTION TO PREVENT SPREAD OF FLAMES

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK & DIKE LRG SPILL. AVOID IGNITION SOURCES SUCH AS FLAME & SPARK. VENT. TRANSFER TO CNTNR FOR DISPOSAL/ RECYCLE. SEAL CNTNR. ABSORB REMAINING SPILL/LEAK W/SAND,EARTH,VERMIC. SWEEP UP, DISPOSE OF ACCORDING TO FEDERAL, STATE & LOCAL REGULATIONS

===== Handling and Storage =====

Handling and Storage Precautio

ns:COMBUSTIBLE-KEEP FROM HEAT/IGNIT

SOURCES. WEAR PROTECT CLOTHING/EQUIP WHEN HANDLING. KEEP CNTNRS SEALED UNTIL USE. AVOID EXCESSIVE STORAGE TEMPS(>52C)

Other Precautions:DONT STORE NEAR STRONG OXIDIZERS. AVOID CONTACT W/SKIN, EYES, CLOTHING. WASH CLOTHING BEFORE REUSE. DONT USE PRESSURE TO EMPTY CONTAINER. WHEN EMPTY, CONTAINER MAY RETAIN PROD RESIDUE. DONT CUT, PUNCT URE OR WELD ON/NEAR DRUM.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:USE NIOSH/MSHA APPROVED RESPIRATOR WITH DUAL ORGANIC VAPOR/MIST AND PARTICULATES CARTRIDGE IF VAPOR CONCENTRATION EXCEEDS PERMISSIBLE EXPOSURE LIMIT.

Protective Gloves:RUBBER OR PLASTIC, SOLVENT RESISTANT

Eye Protection:CHEMICAL SAFETY GOGGLES/FULL FACE SHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>

300F,>149C

Vapor Pres:1

Spec Gravity:.924

Viscosity:>/= 100 @100F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN, BLACK, GRAY THIXOTROPIC LIQUID (OPAQUE); SLIGHT KEROSENE-LIKE ODOR.

Percent Volatiles by Volume:46

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS SUCH AS HYDROGEN PEROXIDE, BROMINE AND CHROMIC ACID.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

FROM BURNING. OXIDES

OF SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DIPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for i

ts use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.