

QUICK START PRODUCTS LTD -- ETHER -- 1730-01-182-0364

=====
Product Identification
=====

Product ID:ETHER
MSDS Date:05/01/1991
FSC:1730
NIIN:01-182-0364
MSDS Number: BQFFF
=== Responsible Party ===
Company Name:QUICK START PRODUCTS LTD
Address:HWY 251 S
City:ROCHELLE
State:IL
ZIP:61068
Country:US
Info Phone Num:815-562-5414
Emergency Phone Num:815-562-5414
CAGE:78280
=== Contractor Identification
===
Company Name:QUICK START PRODUCTS LTD
Address:HIGHWAY 251 SOUTH
Box:City:ROCHELLE
State:IL
ZIP:61068
Country:US
Phone:815-562-5414
CAGE:78280

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ETHER (SARA III)
CAS:60-29-7
RTECS #:KI5775000
Fraction by Wt: 91%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400PPM/500STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE (SARA III)
CAS:74-85-1
RTECS #:KU5340000
Fr

action by Wt: 6.5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:ASPHYXIAN; 9293

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9293

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL
CAS:128-37-0
RTECS #:GO7875000
Fraction by Wt: .001%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3; 9293

===== Hazards Identification =====

LD50 LC50 Mixt
ure:TLV=400PPM;STEL=500PPM ETHER,RTEC 92-4
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE
CONJUNCTIVITIS.INHAL:RESPIRATORY
IRRITATION,HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,SLEEPINESS.
Explanation of Carcinogenicity:HMS FOUND A MONOGRAPH ON DIETHYL ETHER
IN RTECS 92-4,SHOWING DNA MUTATION IN E.COLI.
Effects of Overexposure:MFG STATES THAT CASUAL EXPOSURE SHOULD HAVE NO
ADVERS
E
EFFECTS.INHAL:HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,VOMITING,SLEEPINES
S.
Medical Cond Aggravated by Exposure:NONE REPORTED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INGEST:IF CONSCIOUS,GIVE MILK OR WATER.DON'T GIVE ANYTHING
ACIDIC(EG.JUICE).CALL PHYSICIAN.INDUCE VOMITING ONLY! IF ADVISED BY
TREATING PHYSICIAN.INHAL:REMOVE TO FRESH AIR.RESTORE BREATHING BY
MOUTH-T O-MOUTH RESPIRATION(PREFERRABLY).CALL PHYSICIAN.EYES:FLUSH

WITH WATER FOR 15 MINUTES.DO NOT RUB EYES!SKIN:REMOVE CONTAMINATED CLOTHING.FLUSH WITH WATER.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:-49F,-45C

Lower Limits:1.9

Upper Limits:48

Extinguishing Media:DRY CHEMICAL,FOAM,CARBON DIOXIDE.

Fire Fighting Procedures:WATER IS INEFFECTIVE IN FIGHTING A FIRE,BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.USE A SCBA IN POSITIVE PRESSURE MODE.FLUSH AWAY SPILLS NOT IGNITED.

Unusual Fire/Explosion Hazard:VAPORS TRAVEL AND ARE A FLASH-BACK HAZARD.RUNOFF TO SEWERS ARE FIRE/EXPLOSION HAZARD.FIRE PRODUCES SMOKE AND HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.VENTILATE.FLUSH LARGE SPILLS WITH WATER;AVOID RUNOFF TO SEWERS.ADSORB SMALL SPILLS WITH AN INERT MATERIAL;PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL,OR ALLOW TO EVAPORATE (USING GOOD VENTILATION).

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 175F.KEEP AWAY FROM SOURCES OF COMBUSTION AND COMBUSTIBLE MATERIALS.PREVENT DAMAGE TO CONTAINERS.KEEP AWAY FROM RESIDENTIAL STRUCTURES.

Other Precautions:NO SMOKING IN STORAGE AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR WHEN HIGH CONCENTRATIONS ARE PRESENT.

Ventilation:NATURAL VENTILATION IS PREFERRED.ENGINEERING CONTROLS MUST BE EXPLOSION PROOF IF USED.

Protective Gloves:FOR PROLONGED USE-NITRILE

Eye Protection:GOGGLES MEETING ANSI 287.1

Other Protective Equipment:IF SKIN CONTACT IS ANTICIPATED USE NITRILE COATED CLOTHING.

Work Hygienic Practices:USE PRUDENT HYGENIC AND SANITARY PRACTICES.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:94.0F,34.4C

Vapor Pres:7.3ATM

Vapor Density:2.6

Spec Gravity:.695

Evaporation Rate & Reference:6.9

Solubility in Water:MODERATE

Appearance and Odor:AEROSOL;COLORLESS;ETHER-LIKE ODOR(SWEET-PUNGENT)

Percent Volatiles by Volume:>98

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS,CHEMICALS THAT UNDERGO SPONTANEOUS COMBUSTION.

Stability Condition to Avoid:TEMPERATURES ABOVE 175F,FLAMES,SOURCES OF
IGNITION.EXPLOSIVE PEROXIDES FORM

AS PRODUCT AGES/CONCENTRATES.

Hazardous Decomposition Products:CARBON MONOXIDE,VARIOUS ALDEHYDES.

===== Disposal Considerations =====

Waste Disposal Methods:1-ALLOW SMALL AMOUNTS TO EVAPORATE.2-USE
CONTENTS COMPLETELY,THEN DISPOSE OF IN NORMAL TRASH;DO NOT PUNCTURE
OR INCINERATE CANS.FOLLOW FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t
he Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.