

QUICK START PRODUCTS LTD -- ETHER -- 1730-01-182-0364

=====  
Product Identification  
=====

Product ID:ETHER  
MSDS Date:05/01/1991  
FSC:1730  
NIIN:01-182-0364  
MSDS Number: BQFFF  
=== Responsible Party ===  
Company Name:QUICK START PRODUCTS LTD  
Address:HWY 251 S  
City:ROCHELLE  
State:IL  
ZIP:61068  
Country:US  
Info Phone Num:815-562-5414  
Emergency Phone Num:815-562-5414  
CAGE:78280  
=== Contractor Identification  
===  
Company Name:QUICK START PRODUCTS LTD  
Address:HIGHWAY 251 SOUTH  
Box:City:ROCHELLE  
State:IL  
ZIP:61068  
Country:US  
Phone:815-562-5414  
CAGE:78280

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ETHER (SARA III)  
CAS:60-29-7  
RTECS #:KI5775000  
Fraction by Wt: 91%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400PPM/500STEL; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE (SARA III)  
CAS:74-85-1  
RTECS #:KU5340000  
Fr

action by Wt: 6.5%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:ASPHYXIAN; 9293

Ingred Name:ETHYL ALCOHOL (ETHANOL)  
CAS:64-17-5  
RTECS #:KQ6300000  
Fraction by Wt: 2.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM; 9293

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL  
CAS:128-37-0  
RTECS #:GO7875000  
Fraction by Wt: .001%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3  
ACGIH TLV:10 MG/M3; 9293

=====  
===== Hazards Identification =====

LD50 LC50 Mixt  
ure:TLV=400PPM;STEL=500PPM ETHER,RTEC 92-4  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES:MAY CAUSE  
CONJUNCTIVITIS.INHAL:RESPIRATORY  
IRRITATION,HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,SLEEPINESS.  
Explanation of Carcinogenicity:HMS FOUND A MONOGRAPH ON DIETHYL ETHER  
IN RTECS 92-4,SHOWING DNA MUTATION IN E.COLI.  
Effects of Overexposure:MFG STATES THAT CASUAL EXPOSURE SHOULD HAVE NO  
ADVERS  
E  
EFFECTS.INHAL:HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,VOMITING,SLEEPINES  
S.  
Medical Cond Aggravated by Exposure:NONE REPORTED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INGEST:IF CONSCIOUS,GIVE MILK OR WATER.DON'T GIVE ANYTHING  
ACIDIC(EG.JUICE).CALL PHYSICIAN.INDUCE VOMITING ONLY! IF ADVISED BY  
TREATING PHYSICIAN.INHAL:REMOVE TO FRESH AIR.RESTORE BREATHING BY  
MOUTH-T O-MOUTH RESPIRATION(PREFERRABLY).CALL PHYSICIAN.EYES:FLUSH

WITH WATER FOR 15 MINUTES.DO NOT RUB EYES!SKIN:REMOVE CONTAMINATED CLOTHING.FLUSH WITH WATER.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:-49F,-45C

Lower Limits:1.9

Upper Limits:48

Extinguishing Media:DRY CHEMICAL,FOAM,CARBON DIOXIDE.

Fire Fighting Procedures:WATER IS INEFFECTIVE IN FIGHTING A FIRE,BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.USE A SCBA IN POSITIVE PRESSURE MODE.FLUSH AWAY SPILLS NOT IGNITED.

Unusual Fire/Explosion Hazard:VAPORS TRAVEL AND ARE A FLASH-BACK HAZARD.RUNOFF TO SEWERS ARE FIRE/EXPLOSION HAZARD.FIRE PRODUCES SMOKE AND HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.VENTILATE.FLUSH LARGE SPILLS WITH WATER;AVOID RUNOFF TO SEWERS.ADSORB SMALL SPILLS WITH AN INERT MATERIAL;PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL,OR ALLOW TO EVAPORATE (USING GOOD VENTILATION).

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 175F.KEEP AWAY FROM SOURCES OF COMBUSTION AND COMBUSTIBLE MATERIALS.PREVENT DAMAGE TO CONTAINERS.KEEP AWAY FROM RESIDENTIAL STRUCTURES.

Other Precautions:NO SMOKING IN STORAGE AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR WHEN HIGH CONCENTRATIONS ARE PRESENT.

Ventilation:NATURAL VENTILATION IS PREFERRED.ENGINEERING CONTROLS MUST BE EXPLOSION PROOF IF USED.

Protective Gloves:FOR PROLONGED USE-NITRILE

Eye Protection:GOGGLES MEETING ANSI 287.1

Other Protective Equipment:IF SKIN CONTACT IS ANTICIPATED USE NITRILE COATED CLOTHING.

Work Hygienic Practices:USE PRUDENT HYGENIC AND SANITARY PRACTICES.

Supplemental Safety and Health  
NONE.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:94.0F,34.4C

Vapor Pres:7.3ATM

Vapor Density:2.6

Spec Gravity:.695

Evaporation Rate & Reference:6.9

Solubility in Water:MODERATE

Appearance and Odor:AEROSOL;COLORLESS;ETHER-LIKE ODOR(SWEET-PUNGENT)

Percent Volatiles by Volume:>98

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS,CHEMICALS THAT UNDERGO SPONTANEOUS COMBUSTION.

Stability Condition to Avoid:TEMPERATURES ABOVE 175F,FLAMES,SOURCES OF  
IGNITION.EXPLOSIVE PEROXIDES FORM

AS PRODUCT AGES/CONCENTRATES.

Hazardous Decomposition Products:CARBON MONOXIDE,VARIOUS ALDEHYDES.

===== Disposal Considerations =====

Waste Disposal Methods:1-ALLOW SMALL AMOUNTS TO EVAPORATE.2-USE  
CONTENTS COMPLETELY,THEN DISPOSE OF IN NORMAL TRASH;DO NOT PUNCTURE  
OR INCINERATE CANS.FOLLOW FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t  
he Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.