

PRATT AND LAMBERT INC -- LACQUER C/N GLOSS CLEAR ID 786800 -- 8010-00-251-6495

=====
Product Identification
=====

Product ID:LACQUER C/N GLOSS CLEAR ID 786800

MSDS Date:08/11/1992

FSC:8010

NIIN:00-251-6495

MSDS Number: BQGMK

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:873-6000 DOT EMER 8002553924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200

PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III) (SOLVENT) (LFL 1.0; UFL 11.0)
(VAPOR PRESSURE 10 MM HG @ 20C)

CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VM&P NAPHTHA (VAPOR PRESSURE 40 MM HG @ 20C) (LFL:1.0 UFL:
6.0)

CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 5%
Other REC Limits:
NONE SPECIFIED
OSHA PEL:300 PPM;STEL 400 PPM
ACGIH TLV:300 PPM; 1350 MG/M3

Ingred Name:ISOPROPYL ALCOHOL (SARA III) (SOLVENT) (LFL 3.0; LFL 13.0)
(VAPOR PRESSURE 33 MM HG @ 20C)

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/STEL 500 PPM
ACGIH TLV:400 PPM/STEL 500 PPM

Ingred Name:NITROCELLULOSE (RESIN)

CAS:9004-70-0
RTECS #:QW9700000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED

Ingred Name:DI(2-ETHYLHEXYL)PHTHALATE (ADDITIVE) (SAR

A III)
CAS:117-81-7
RTECS #:TI0350000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ISOBUTYL ACETATE (SARA III) (SOLVENT) (LFL 2.0; UFL 11.0)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM; 700 MG/M3
ACGIH TLV:150 PPM; 700 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE (SOLVENT) (LFL 1.0; UFL 7.0) (VAPOR PRESSURE 40
MM HG @ 20C)
CAS:142-82-5
RTECS #:MI770000
0
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:HEXANE (SOLVENT) (LFL 1.0; UFL 8.0) (VAPOR PRESSURE 120 MM
HG @ 20C)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: AIR
Spec Gravity:0.9
pH:4-7STD
Viscosity:> 200 CST
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT IN WATER
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:78 %

===== Stability and R

activity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT (>115F) AND SOURCES OF IGNITION.

Hazardous Decomposition Products: SMOKE, CO, CO₂. OXIDES OF NITROGEN MAY BE GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods: PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR

LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.