View NSN Online: https://aerobasegroup.ae/nsn/3439-00-878-2150

J.W.HARRIS CO.INC. -- 308-15 ELECTRODE -- 3439-00-878-2150

=========== Product Identification ==============

Product ID:308-15 ELECTRODE

MSDS Date:08/01/1990

FSC:3439

NIIN:00-878-2150

MSDS Number: BQKQB === Responsible Party ===

Company Name: J.W.HARRIS CO.INC. Address: 10030 DEERFIELD ROAD

City:CINCINNATI

State:OH ZIP:45242 Country:US

Info Phone Num:513-891-2000

Emergency Phone Num:513-891-2000

CAGE:27911 === Con

tractor Identification ===

Company Name: J. W. HARRIS CO., INC.

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

======= Composition/Information on Ingredients ========

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500

Fraction by Wt: BALENCE
Other REC Limits:NONE
OSHA PEL:10MG/M3(FE203)
ACGIH TLV:5MG/M3(FE203)

Ingred Name: CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000 Fraction by Wt: 18-21% Other REC Limits:NONE OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000 Fraction by Wt: 9-12% Other REC Limits:NONE OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name: MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000 Fraction by Wt: 0.5-2.5% Other REC Limits:NONE OSHA PEL:(C) 5 MG/M3

OSHA PEL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name: SILICON

CAS:7440-21-3

RTECS #:VW0400000 Fraction by Wt: 0.9% Other REC Limits:NONE

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000 Fraction by Wt: 0.75-3% Other REC Limits:NONE OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingred Name: COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000 Fraction by Wt: 0.75% Other REC Limits:NONE

OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100 Fraction by Wt: .04-.08%

Other

ACGIH TLV:2 MG/M3 TDUST; 9293
======================================
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT. CHRONIC: EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG FIBROSIS,PNEUMOCONIOSIS. LONG TERM EXPO S URE TO IRON FUMES MAY PRODUCE SIDEROSIS. ARC RAYS MAY INJURE EYE & BURN SKIN. ELECTRIC SHOCK CAN KILL. Explanation of Carcinogenicity:CHROMIUM, NICKEL AND SOME OF THEIR COMPOUNDS ARE LISTED AS CARCINOGENS BY NTP & IARC. SEE INDIVIDUAL REPORTS FOR DATA.
Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED PULMONAARY FUNCTIONS OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY FUME IRRITANTS,
======================================
First Aid:REMOVE FROM DUST AND FUME EXPOSURE. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. SUMMON MEDICAL AID IMMEDIATELY.
======================================
Extinguishing Media:SUPPLIER DID NOT ADDRESS THIS FIELD. Fire Fighting Procedures:SUPPLIER DID NOT ADDRESS THIS FIELD. Unusual Fire/Explosion Hazard:WELDING ARCS, OPEN FLAME AND SPARKS CAN IGNITE COMBUSTIBLES. SEE ANSI/ASC Z49.1-1983 SECTION 6.
==== =================================
Spill Release Procedures:"NOT APPLICABLE" Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER
========== Handling and Storage ============
Handling and Storage Precautions:NO INFORMATION GIVEN ON MSDS BY SUPPLIER Other Precautions:READ AND LINDERSTAND THE MANUFACTURER'S INSTRUCTIONS

AND THE PRECAUTIONARY LABEL ON THE PRODUCT. SEE AMSI STANDARD Z49.1

AND 29CFR1910 FOR DETAILS ON MANY PRECA

REC Limits:NONE

OSHA PEL:15 MG/M3 TDUST

KEEP HIS HEAD OUT OF FUMES. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEBN WELDING IN CONFINED SPACES OR WHERE LOCAL EXHAUST OT VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation: USE ENOUGH VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE AT OPERATOR'S BREATHING ZONE AND THE GENERAL AREA BELOW TLV Protective Gloves: WELDER'S GLOVES. ye Protection: HELMET OR FACE SHIELD WITH FILTER LENS. Other Protective Equipment: MAY ALSO INCLUDE ARM PROTECTOR, APRON, HAT, SHOULDER PROTECTION. SEE SUPP DATA. Work Hygienic Practices: WASH HANDS THOROUGHLY BEFORE EATING, SMOKEING, USING SANITARY FACILITIES. Supplemental Safety and Health PROVIDE SCREENS AND FLASH GOGGLES TO PROTECT OTHER INDIVIDUALS FROM BEING EXPOSED TO THE RADIATION FROM THE ELECTRIC ARC. ========= Physical/Chemical Properties =========== HCC:N1 NRC/State Lic Num:NONE Solubility in Water: INSOLUBLE Appearance and Odor:WELDING ROD.NO ODOR. 0.125 INCH DIAMETER BY 14 INCHES LONG. ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products: WELDING & BRAZING FUMES CANNOT BE CLASSIFIED SIMPLY. COMPOSITION AND QUANTITY DEPEND ON BASE METAL.FILLER METAL AND USE. ========= Disposal Considerations ================= Waste Disposal Me

UTIONS. TRAIN EMPLOYEE TO

thods:"NOT APPLICABLE" HMIS: DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.