

ALDRICH CHEMICAL CO INC. -- 27063-6 CHLOROFORM, HPLC GRADE -- 6810-00-973-6472

=====  
Product Identification  
=====

Product ID:27063-6 CHLOROFORM, HPLC GRADE

MSDS Date:08/17/1987

FSC:6810

NIIN:00-973-6472

MSDS Number: BQKQS

=== Responsible Party ===

Company Name:ALDRICH CHEMICAL CO INC.

Address:1001 W. ST. PAUL AVE

Box:2060

City:MILWAUKEE

State:WI

ZIP:53201

Country:US

Info Phone Num:414-273-3850 FA

X: 414-273-4979

Emergency Phone Num:414-273-3850

CAGE:60928

=== Contractor Identification ===

Company Name:ALDRICH CHEMICAL CO INC

Address:1001 WEST ST PAUL AVE

Box:355

City:MILWAUKEE

State:WI

ZIP:53233

Country:US

Phone:414-273-3850

CAGE:60928

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CHLOROFORM (SARA III)

CAS:67-66-3

RTECS #:FS9100000

Fraction by Wt: 99.9%+

Other REC Limits:TRANS PEL:50 PPM, C

OSHA PEL:(C) 50 PPM

ACGIH TLV:10 PPM; A2; 9293

EPA Rpt Qty:10

LBS  
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 908 MG/M3  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:HIGHLY TOXIC! CARCINOGEN! ACUTE:MAY  
BE FATAL IF INHALED, INGESTED OR ABSORBED THROUGH SKIN. VAPOR/MIST  
IS IRRIT TO EYES, MUCOUS MEMBRANES & UPPER RESP TRACT. CAUSES SKIN  
IRRITATION. CHRONIC:CARCINOGEN. DAMAGE TO LIVER, KIDNEYS AND  
HEART.EXPOSURE TO AND/OR CONSUMPTION OF ALCOHOL MAY INCREASE TOXIC  
EFFECTS.  
Explanation of Carcinogenicity:CHLOROFORM IS LISTED BY NTP AND IARC.  
SEE INDIVIDUAL REPORTS FOR DETAILS.  
Effects of Overexposure:NAUSEA, DIZZINESS AND HEADACHE. MAY CAUSE  
NERVOUS SYSTEM DISTURBANCES.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH W/  
COPIOUS AMTS OF WATER FOR AT LEAST  
15 MINUTES. SKIN:IMMEDIATELY FLUSH W/COPIOUS AMTS OF WATER FOR 15  
MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. WASH  
CONTAMINATED CLOTHING BEFORE REUSE. INHAL:REMOVE TO FRESH AIR.  
SUPPORT BREATHING (GIVE O2/ARTF RESP) CALL MD. INGEST:RINSE MOUTH  
W/WATER. DO NOT INDUCE VOMIT. DRINK 8-10 OZ WATER. CALL MD  
IMMEDIATELY .

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:NON  
COMBUSTIBLE. USE EXTINGUISHING MEDIA APPROPRIATE  
TO SURROUNDING FIRE CONDITIONS.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA  
AND FULL PROTECTIVE EQUIPMENT TO PREVENT CONTACT WITH SKIN AND  
EYES.  
Unusual Fire/Explosion Hazard:EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA. WEAR SCBA, RUBBER BOOTS & HEAVY  
RUBBER GLOVES. ABSORB ON SAND OR VERMICULITE & PLA

CE IN CLOSED

CONTAINERS FOR DISPOSAL. VENTILATE AREA & WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE.

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP TIGHTLY CLOSED. PROTECT FROM LIGHT. DO NOT BREATHE VAPOR. AVOID ALL CONTACT.

Other Precautions:NONE

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:

WEAR APPROPRIATE NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation:USE ONLY IN A CHEMICAL FUME HOOD.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING. SAFETY SHOWER AND EYE BATH.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.DO NOT GET IN EYES, ON SKIN, ON CLOTHING.

Supplemental Safety and Health

MSDS RECEIVED FROM NAVY (FOCAL POINT N). CAGE CODE AND NSN IDENTIFIED BY THEM.

=====  
Physical/Chemical Properties  
=====

HCC:T3

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:141F,61C

Melt/Freeze Pt:M.P/F.P Text:-81F,-63C

Vapor Pres:160 MM

Vapor Density:4.1

Spec Gravity:1.492

Appearance and Odor:NO INFORMATION GIVEN ON MSDS BY MFR.

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

BASES, ALUMINUM,

Stability Condition to Avoid:SENSITIVE TO LIGHT.

Hazardous Decomposition Products:TOXIC FUMES OF:HYDROGEN CHLORIDE GA

S,  
PHOSGENE GAS, CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: MATL SHOULD BE IGNITED IN PRESENCE OF SODIUM CARBONATE & SLAKED LIME (CALCIUM HYDROXIDE). SUBSTANCE SHOULD BE MIXED W/ VERMICULITE & THEN W/ DRY CAUSTICS, WRAPPED IN PAPER & BURNED IN CHEMICAL INCINERATOR EQUIPPED W/ AFTERBURNER & SCRUBBER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.