View NSN Online: https://aerobasegroup.com/nsn/6810-00-006-4206

ASHLAND CHEMICAL COMPANY -- ETHYLENE GLYCOL TECH -- 6810-00-006-4206

========= Product Identification ============

Product ID:ETHYLENE GLYCOL TECH

MSDS Date: 05/31/1989

FSC:6810

NIIN:00-006-4206

MSDS Number: BQLYQ === Responsible Party ===

Company Name: ASHLAND CHEMICAL COMPANY

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Info Phone Num:614-790-3333

Emergency Phone Num:800-274-5263

CAGE:34897

===

Contractor Identification ===

Company Name: ASHLAND CHEMICAL CO

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Phone:614-790-3333/800-274-5263

CAGE:34897

Company Name: DIXCO DIVERSIFIED

Address:847 S EAST STREET

Box:City:ANAHEIM

State:CA ZIP:92805 Country:US

Phone:714-535-0646

CAGE:0FJJ3

Company Name: TEXAS INSTRUMENTS INC DEFENSE SYSTEM & ELECTRONICS

Address:8505 FOREST LN

Box:660246 City:DALLAS State:TX

ZIP:75266-0246 Country:US CAGE:96214

====== Composition/Information on In

| gredients ========= |
|---|
| Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 |
| Fraction by Wt: 100% |
| Other REC Limits:NONE SPECIFIED |
| OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 |
| EPA Rpt Qty:1 LB |
| DOT Rpt Qty:1 LB |
| ====================================== |
| LD50 LC50 Mixture:PEL=50PPM;TLV=50PPM (BOTH CEILING) |
| Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES |
| Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EY |
| ES:IRRITANT.SKIN:SLIGHT |
| IRRITANT.INHAL:NASAL AND RESPIRATORY IRRITATION.INGEST:CAN CAUSE |
| GASTROINTESTINAL IRRITATION.CHRONIC EFFECTS ARE BIRTH |
| DEFECTS,KIDNEY AND LIVER DAMAGE AND CENTRAL NERVOUS SYS TEM EFFECTS. |
| Explanation of Carcinogenicity:RTECS 92-4 SHOWS MONOGRAPHS ON ETHYLENE |
| GLYCOL AS A MUTAGEN, TUMORIGEN, REPRODUCTIVE EFFECTOR. |
| Effects of Overexposure:INGEST:NAUSEA,VOMITING,DIARRHEA. Medical Cond Aggravated by Exposure:HMIS SUGGESTS THAT PERSONS WITH A |
| HISTORY OF KI |
| DNEY OR LIVER DISORDERS MAYBE AT INCREASED RISK FROM EXPOSURE. |
| ====================================== |
| First Aid:EYE:FLUSH W/ WATER 15 MIN HOLD LIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:GIVE 2 GLASSES WATER AND INDUCE VOMITING(BYIPECAC OR FINGER DOWN THROAT). GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET |
| IMMEDIATE MEDICAL C ARE. IF IRRITATION PERSISTS,OR IS SEVERE,SEE A DOCTOR. |
| ====================================== |
| Flash Point Method:TCC |
| Flash Point:232F,111C |
| Lower Limits:3.2 |
| Upper Limits:15.3 Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL, OR WATER |
| FOG.WATER OR FOAM MAY CAUSE FROTHING. |
| Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A |
| FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRA |

| Y. |
|---|
| Unusual Fire/Explosion Hazard:CONTAINERS ARE AN EXPLOSION HAZARD. |
| ======== Accidental Release Measures ========== |
| Spill Release Procedures:WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBENT. PUT IN DISPOSAL CONTAINER. FLUSH RESIDUE WITH WATER. LARGE SPILL: VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUI D. FLUSH RESIDUE WITH WATER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
| e ==================================== |
| Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE. Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. DO NOT PRESSURIZE,CUT,WELD,BRAZE,ETC. NEAR THEM. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC DUST/MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE. Ventilation:NORMAL VENTILATION IS USUALLY SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED. Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. AVOID PROLONGED AND/OR REPEATED CONTACT BY USING APPROPRIATE CLOTHING Work Hygienic Pra ctices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING. Supplemental Safety and Health POISONOUS. |
| ========= Physical/Chemical Properties ========== |
| HCC:V5 Boiling Pt:=192.8C, 379.F Vapor Pres:0.1 Vapor Density:2.2 Spec Gravity:1.115 Evaporation Rate & Description Reference: |