

DESOTO AEROSPACE COATINGS, INC -- PRIMER GREEN LOW IR 515X370 -- 8010-01-050-4082
===== Product Identification =====

Product ID:PRIMER GREEN LOW IR 515X370

MSDS Date:02/12/1991

FSC:8010

NIIN:01-050-4082

Kit Part:Y

MSDS Number: BQMJQ

=== Responsible Party ===

Company Name:DESOTO AEROSPACE COATINGS, INC

Address:1608 FOURTH STREET

City:BERKELEY

State:CA

ZIP:94710

Country:US

Info Phone Num:818-549-78

23

Emergency Phone Num:800-424-9300(CHEMTREC)/800-228-5635

CAGE:DESOT

=== Contractor Identification ===

Company Name:DESOTO AEROSPACE COATINGS, INC

Address:1608 FOURTH STREET

City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:818-549-7822

CAGE:DESOT

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

Box:City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

===== Composition/Information on Ingredients =====

==

Ingred Name:XYLENE (SARA 313) (VAPOR PRESSURE 10 MM HG)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150 STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313) (VAPOR PRESSURE 7.1 MM HG)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125 STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUE

NE (SARA 313) (VAPOR PRESSURE 22 MM HG)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313) (VAPOR PRESSURE 33 MM HG)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500 STEL

Ingred Name:POLYMAMIDE RESIN

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 7.11 (GRAMS/LITER)

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES

Health Hazards Acute and Chronic:INHAL: NASAL/RESP IRRIT AND ACUTE CNS

DEPRESS W/HEADACHE-DIZZINESS-STAGGERING

GAIT-CONFUSION-UNCONSCIOUSNESS. ASPHYXIATION FROM BREATHING OXYGEN

DEFICIENT AIR. SKIN: IRRIT-DEFAT- DERMATITIS. SKIN

SENS ITIZATION.

EYE: IRRIT. INGEST: GI-NAUSEA-VOMITING- DIARRHEA. ASPIR OF MATL

INTO LUNGS MAY CAUSE CHEM PNEUMONITIS-FATAL.

Explanation of Carcinogenicity:HEXAVALNT CHROMIUM COMPOUND AND

CRYSTALLINE SILICA ARE LISTED AS CARCINOGENS BY IARC AND NTP.

Effects of Overexposure:PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

CONCENTRATION DIFFICULTIES-DIMINISHED ACTUAL DEXTERITY-MEMORY LOSS.

LIVER- KIDNEYS-LUNG-SPLEEN DAMAGE.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN, LUNG

AND EYE

CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR FROM EXPOSURE. GIVE ARTIFICIAL

RESPIRATION OR CPR IF REQUIRED. IF BREATHING IS DIFFICULT, GIVE

OXYGEN. KEEP WARM AND QUIET. GET MED ATTN. SKIN: WASH AFFECTED

AREAS WITH SOAP AND WATER. DO NOT USE SOLVENTS. REMOVECONTAMINATED

CLOTHING-WASH BEFORE REUSE. GET MED ATTN. EYE: FLUSH WITH WATER 15

MINS. GET MED ATTN- PREFERRABLY FROM AN OPHTHALMOLOGIS

T. INGEST:

GET MED ATTN

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:45.0F,7.2C

Lower Limits:1 %

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE-COOL FIRE EXPOS

CNTNR W/WTR. FOG NOZZLES PREFERRED. WEAR NIOSH/MSHA SCBA AND

PROTECTIVE CLOTHING TO PREVENT CONTACT W/SKIN & EYES

Unusual Fire/Explosion Hazard:VAPORS MAY ACCUMULATE IN POOR

VENT/CONFINED AREAS. VA

PORS FORM EXPLOS MIX W/AIR-MAY TRAVEL
DISTANCES. FLASHBACK/FLAME TO HNDLING SITE. CLSD CNTNR EXPLODE
W/HEAT

===== Accidental Release Measures =====

Spill Release Procedures:DEPEND ON QTY-CIRCUMSTANCES, REPORTABLE UNDER
FED LAW. CK W/STATE/LOCAL GOVT. RMV IGNIT SRCS. WEAR PERSONAL
PROTECT EQUIP-AVOID BREATH VAPORS-SKIN/EYE CONTACT. NON-SPARK
TOOLS. EXCESS QTY-USE EMER RES PONSE PROFESSIONAL. SM: DIKE/ABSORB
W/INERT MATL

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNR CLSD TIGHT-AWAY FROM
HEAT-IGNIT SRCS. DONT STORE >49C. STORE FLAMM LIQ IN ACCORD W/NFPA.
FOLLOW GROUND/BOND REQ W/TRANS-AVOID LIQ FREE FALL

Other Precautions:EMPTY DRUMS HOLD EXPLOS VAPORS. DONT
CUT-PUNCTURE-WELD ON/NEAR DRUM. DONT INGEST-INHAL CONC VAPORS.
PREVENT PROLONG CONTACT W/ CONTAM CLOTH-WASH BEFORE REUSE. VAPORS
COLLECT IN LOW/CONFINED AREA. FOLL OW ALL APPROP PROCED BEFORE

ENTERING ARE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:TLVS EXCEEDED OR SPRAY MIST-USE NIOSH/MSHA
RESPIRATORY PROTECTION FOR INDICATED COMPONENTS. CONFINED
AREAS-NIOSH/MSHA AIR SUPPLIED RESPIRATORS. FOLLOW RESPIRATOR MFR
DIRECTIONS AND OSHA REGULATIONS (2 9 CFR 1910.134) FOR RESPIRATOR
USE.

Ventilation:GENERAL DILUTION/LOCAL EXHST IN VOL/PATTRN TO KEEP LEVEL
BELOW TLV OR PEL LIMIT. UNEXPOSED: KEEP LEVEL BELOW 25% OF LEL

Pro

tective Gloves:CHEMICALLY RESISTANT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER
PROTECTIVE CLOTHING. A SAFETY SHOWER-EYE BATH-WASHING FACILITIES
SHOULD BE AVAILABLE

Supplemental Safety and Health

KEY1;F5.DO NOT SMOKE WHERE THIS MATERIAL IS USED OR STORED. DO NOT
APPLY TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:180-277F

Vapor Density:> THAN

AIR
Spec Gravity:0.87
Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC
Appearance and Odor:CLEAR LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:84.2%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS
INCLUDING CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ENSURE MATL IS
PACKAGED-STORED-TRANSPORTED AND
OTHERWISE MANAGED IN ACCORD W/LOCAL-STATE AND FEDERAL REGULATIONS.
NO DISPOSAL METHOD IS TO BE USED THAT WOULD POSE
ENVIRONMENTAL/HUMAN HEALTH THREAT INC LUD ANY WHICH WOULD
CONTAMINATE GROUND/SURFACE WTR

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this
information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.