

FLEXABAR CORPORATION -- WB1003 BLACK -- 8030-01-154-2327

=====
Product Identification
=====

Product ID:WB1003 BLACK

MSDS Date:10/01/1986

FSC:8030

NIIN:01-154-2327

MSDS Number: BQNRT

=== Responsible Party ===

Company Name:FLEXABAR CORPORATION

Address:140 WALNUT STREET

City:NORTHVALE

State:NJ

ZIP:07647

Country:US

Info Phone Num:201-768-5570

Emergency Phone Num:201-768-5570

CAGE:18354

=== Contractor

Identification ===

Company Name:FLEXABAR CORPORATION

Address:140 WALNUT STREET

Box:City:NORTHVALE

State:NJ

ZIP:07647

Country:US

Phone:201-768-5570

CAGE:18354

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL MONOETHYL ETHER

CAS:111-90-0

RTECS #:KK8750000

Other REC Limits:NONE SPECIFIED

Ingred Name:VINYL CHLOR

IDE (SARA III)
CAS:75-01-4
RTECS #:KU9625000
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1017
ACGIH TLV:5 PPM, A1; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and
Chronic:SUPPLIER LEFT THIS FIELD BLANK.
UNDER "ROUTES OF ENTRY" MFR LISTED EYES:CAUSES IRRITATION.
SKIN:PROLONGED/REPEATED SKIN CONTACTCAUSES MILD IRRITATION.
Explanation of Carcinogenicity:PER MSDS: THIS PRODUCT IS NOT LISTED BY
NTP, IARC, OR OSHA (NO CHECKED FOR EACH AGENCY).
Effects of Overexposure:MAY CAUSE IRRITATION TO EYES OR SKIN.
Medical Cond Aggravated by Exposure:MILD IRRITATION

=====
===== First Aid Measures =====

First Aid:FLUSH EYE/
SKIN WITH SOAP/WATER, CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL FOAM/CO2
Fire Fighting Procedures:TREAT AS A LATEX PAINT NONFLAMMABLE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:DRY OR SOAK UP WITH INERT ABSORBENT; SCOOP
INTO CONTAINER FOR DISPOSAL.
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

=====
===== Ha

Handling and Storage =====

Handling and Storage Precautions:HANDLES AS ALATEX PAINT / WEAR
PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN OR EYES.
Other Precautions:NO INFORMATION GIVEN ON MSDS BY MFR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MANUFACTURER LEFT THIS FIELD BLANK.
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Other Protective Equipment:NOT REQUIRED
Work Hygienic Practices:WASH HAND EVERY TIME YOU USE THE M
ATERIAL.
Supplemental Safety and Health
KEY2:KT

===== Physical/Chemical Properties =====

HCC:N1
NRC/State Lic Num:NONE
Boiling Pt:B.P. Text:245F,118C
Spec Gravity:1.00
Solubility in Water:WATER DILUTEABLE
Appearance and Odor:BLACK WITH A LATEX ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CHLORINE, ACID/OXIDIZING AGENTS
Stability Condition to Avoid:LATEX PAINT - KEEP AWAY FROM OXIDIZING
AGEN
TS
Hazardous Decomposition Products:PVC MAY, UNDER VERY HIGH HEAT, RELEASE
VINYL CHLORIDE, A CANCER SUSPECT AGENT.
Conditions to Avoid Polymerization:WILL NOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of Americ

a in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.