View NSN Online: https://aerobasegroup.ae/nsn/5420-00-588-4897

REMA TIP TOP/NORTH AMERICA INC (FORMER REMACO INC) -- COLD VULCANIZING FLUID,203N --

5420-00-588-4897

============ Product Identification =========================

Product ID:COLD VULCANIZING FLUID,203N

MSDS Date:06/18/1991

FSC:5420

NIIN:00-588-4897

MSDS Number: BQSFQ === Responsible Party ===

Company Name: REMA TIP TOP/NORTH AMERICA INC (FORMER REMACO INC)

Address: 200 PARIS AVENUE

City:NORTHVALE

State:NJ ZIP:07647 Country:U

S

Info Phone Num:800-225-7362/800-334-7362

Emergency Phone Num:800-225-7362/800-424-9300(CHEMTREC)

CAGE:GO624

=== Contractor Identification ===

Company Name: REMA TIP TOP/NORTH AMERICA INC

Address: 200 PARIS AVE

City:NORTHVALE

State:NJ

ZIP:07647-5000

Country:US

Phone:800-334-7362/800-225-7362

CAGE:GO624

Company Name: REMACO INC REMATIP TOP/NORTH AMERICA INC

Address:200 PARIS AVE Box:City:NORTHVALE

State:NJ

ZIP:07647-2205

Country:US

Phone:201-768-8100/800-424-9300(CHEMTREC)

CAGE:03795

Composition/Information on Ingredients ======== Ingred Name:TRICHLOROETHYLENE (SARA III) CAS:79-01-6 RTECS #:KX4550000 Other REC Limits: NONE RECOMMENDED OSHA PEL:100 PPM/100 STEL ACGIH TLV:50 PPM/100,A5STEL;93 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS Ingred Name: NON HAZARDOUS INGREDIENTS Fraction by Wt: BALANCE Other REC Limits: NONE RECOMMENDED LD50 LC50 Mixture:LD 50 ORAL RAT IS 4900-7000 MG/KG Routes of Entry: Inh alation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYE AND SKIN IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION, UNCONSCIOSNESS AND DEATH. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION. ASPIRATION INTO LUNGS AFTER INGESTION MAY CAUSE CHEMICAL P NEUMONITIS WHICH MAY BE FATAL. CHRONIC:DERMATITIS, LIVER AND KIDNEY DAMAGE. Explanation of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects of Overexposure: EYES/SKIN: DISCOMFORT, PAIN, IRRITATION. INHALATION: RESPIRATORY TRACT IRRITATION, DIZZINESS, NAUSEA, HEADACHE, LOSS OF COORDINATION AND EQUILIBRIUM, UNCONSCIOUSNESS. DEATH. INGESTION: MOUTH AND GASTR OINTESTINAL IRRITATION, ALSO SAME SYMPTOMS AS INHALATION. Medical Cond Aggravated by Exposure: INDIVIDUALS WITH A HISTORY OF SKIN, RESPIRATORY ILLNESSES AND LIVER AND KIDNEY DISEASES. d Measures =========== First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. INHALATION: REMOVE

======= First Ai

VICTIM T O FRESH AIR. GIVE OXYGEN/CPR IF NEEDED.SEE DOCTOR. INGESTION: DRINK PLENTY OF WATER IF CONSCIOUS. DO NOT INDUCE VOMITING. SEE DOCTOR IMMEDIATELY. NOTHING BY MOUTH IF UNCONSCIOUS.

====== Fire Fighting Measures =====

===========

Flash Point Method:TCC Flash Point:NONE Lower Limits:8

Upper Limits:52

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: VAPORS (8 TO 52% BY VOLUME) CAN IGNITE IN AIR WITH HIGH ENERGY SPARKS. COMBUSTION CAN PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS SUCH

AS HCL AND PHOSGENE.

=============	Accidental	Release	Measures	
---------------	------------	---------	----------	--

Spill Release Procedures:REMOVE PERSONNEL. ELIMINATE IGNITION SOURCES. VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. ABSORB IN INERT MATERIAL AND PLACE IN APPROPIATE DISPOSAL CONTAINER AND COVER. DO NOT FLUSH TO SEW ER.

========== Handling and Storage ==================

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA. PROTECT FROM HEAT, IGNI

TION SOURCES AND INCOMPATIBLE MATERIALS.

KEEP CONTAINERS CLOSED.

Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. DO NOT ENTER THESE AREAS WITHOUT PROPER PROTECTIVE EQUIPMENT AND AN OBSERVER FOR ASSISTANC E.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IF TLV IS EXCEEDED OR IN CASE OF A SPILL, WEAR NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDG E. USE SCBA OR

AIRLINE RESPIRATOR WITH AUXILIARY SCBA IN PRESSURE DEMAND MODE FOR WORK PERFORMED IN STORAGE VESSELS OR CONFINED AREAS.

Ventilation:MECHANICAL (GENERAL) VENTILATION OR LOCAL EXHAUST VENTILATION AS APPROPIATE TO KEEP EXPOSURE LEVELS BELOW PEL.

Protective Gloves: VITON OR SILVER SHIELD GLOVES.

Eye Protection: SPLASHPROOF GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY

SHOWER.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
VULCANIZING LIQUID HAS IRRITATING ODOR AT HIGH TEMPERATURES. NOTE TO PHYSICIAN: NEVER ADMINISTER ADRENALIN FOLLOWING TRICHLOROETHYLENE OVEREXPOSURE. INCREASED SENSITIVITY OF THE HEART TO ADRENALINE M AY

======== Physical/Chemical Properties ===========

BE CAUSED BY OVEREXPOSURE TO TRICHLOROETHYLENE.

HCC:

T4

Boiling Pt:B.P. Text:188F,87C

Melt/Freeze Pt:M.P/F.P Text:-124F,-86C

Vapor Pres:57.8 @ 68F Vapor Density:4.6 Spec Gravity:1.45

Evaporation Rate & Evaporation R

Solubility in Water:0.11%

Appearance and Odor:CLEAR, MOBILE LIQUID WITH MILDLY SWEET, ETHER-LIKE ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG ALKALIES SUCH AS CAUSTIC SODA AND POTASH, AND OXIDIZERS.

Stability Condition to Avoid:H

IGH HEAT, OPEN FLAMES, HIGH ENERGY

SPARKS, WELDING ARCS.

Hazardous Decomposition Products: CARBON MONOXIDE, HYDROGEN CHLORIDE, PHOSGENE.

======= Disposal Considerations ===========

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. CONTAMINATED ABSORBENT MUST BE DISPOSED OF IN A PERMITTED WASTE MANAGEMENT FACILITY.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.