

FISHER SCIENTIFIC -- HEXANES -- 6810-01-063-4534

=====
Product Identification
=====

Product ID:HEXANES

MSDS Date:02/12/1986

FSC:6810

NIIN:01-063-4534

MSDS Number: BQWGC

=== Responsible Party ===

Company Name:FISHER SCIENTIFIC

Address:1 REAGENT LANE

City:FAIR LAWN

State:NJ

ZIP:07410

Country:US

Info Phone Num:201-796-7100

Emergency Phone Num:201-796-7100;800-424-9300(CHEMTREC)

CAGE:1B464

=== Contrac

tor Identification ===

Company Name:FISHER SCIENTIFIC CO. CHEMICAL MFG DIV

Address:1 REAGENT LANE

Box:City:FAIRLAWN

State:NJ

ZIP:07410-2802

Country:US

Phone:201-796-7100

CAGE:1B464

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 100%

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SUPP DATA:COOL CNTNRS W/FLOODING QTYS OF WATER, APPLY FROM
AS FAR A DISTANCE AS POSSI

BLE. AVOID BRTHG TOX VAPS, (ING 3)
RTECS #:9999999ZZ

Inged Name:ING 2: KEEP UPWIND. EVAC TO A RADIUS OF 1500 FEET FOR
UNCONTROLLABLE FIRES. EVAC DOWNWIND FOR LEAKS (BUREAU OF (ING 4)
RTECS #:9999999ZZ

Inged Name:ING 3:EXPLO, EMER HNDLG OF HAZ MATLS IN SURF
TRANSPORTATION, 1981). WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT
EQUIP.
RTECS #:9999999ZZ

Inged Name:CNDTNS TO AVOID (STAB):CNTNR MAY EXPLO IN HEAT/FIRE. VAP
EXPLOSION HAZ INDOORS, OUTDOORS OR IN SEWERS. RUNOFF (ING 6)
RTEC
S #:9999999ZZ

Inged Name:ING 5: TO SEWER MAY CREATE FIRE OR EXPLOSION HAZARD.
RTECS #:9999999ZZ

Inged Name:EFTS OF OVEREXP: & MUSCLE WEAKNESS. ALCOHOL MAY ENHANCE THE
TOXIC EFFECTS.
RTECS #:9999999ZZ

Inged Name:FIRST AID PROC:(APPROX 15-20 MIN). GET MED ATTN IMMED.
EYES: WASH IMMED W/LRG AMTS OF WATER FOR @ LST 15 MIN, (ING 9)
RTECS #:9999999ZZ

Inged Name:ING 8:OCCASNLy LIFTING UPPER & LOWER LIDS UNTIL NO EVIDENCE
OF CHEM REMAINS. GET MED ATTN. INGEST:DO NOT INDUCE(ING 10)
RT
ECS #:9999999ZZ

Inged Name:ING 9: VOMITING. GET IMMEDIATE MEDICAL ATTENTION.
RTECS #:9999999ZZ

Inged Name:SPILL PROC:PRACTICAL & EFFTIVE IN ORDER TO REDUCE THE
CONTAM & THE AMT OF MATL TO DISP.NO SMOKING, FLAMES/FLARES(ING 12)
RTECS #:9999999ZZ

Inged Name:ING 11: IN THE HAZARD AREA. KEEP UNNECESSARY PEOPLE AWAY;
ISOLATE HAZARD AREA AND DENY ENTRY.
RTECS #:9999999ZZ

Inged Name:RESP PROT:ESCAPE: GAS-MASK W/ORGANIC VAP CANISTER
(CHIN-STYLE OR FRONT OR BACK-MOUNTED CANISTER). SEL

F-CONTAINED(ING
14)
RTECS #:9999999ZZ
Other REC Limits:N/L

Ingred Name:ING 13: BREATHING APPARATUS. FIREFIGHTING: SELF-CONTAINED
BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED (ING 15)
RTECS #:9999999ZZ

Ingred Name:ING 14: IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.
RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP: APPROP PROT (IMPERVIOUS) CLOTHING AND
EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT.
RTECS #:9999999ZZ

=====
n =====
=====
Hazards Identificatio

LD50 LC50 Mixture:LD50:(ORAL,RAT) 28710 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:IRRIT/NEUROTOXIN. 5000 PPM IMMEDIATELY
DANGEROUS TO LIFE OR HLTH. ACUTE:LIGHTHEADEDNESS, NAUSEA, VOMITING,
NARCOSIS, HEADACHE, IRRITATION OF THE UPPER RESPIRATORY TRACT. CHRONIC:PROLONGED EXPOSURE
MAY CAUSE PERIPHERAL NEUROPATHY & CARDIAC SENSITIZATION.
SKIN:IRRITANT/NARCOTIC. ACUTE:PROLONGED CONTACT MAY PRODUCE MODERATE IRRITATION.
MAY BE ABSORBED, (EFFECTS OF OVEREXPOSURE)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HEALTH HAZARD:PRODUCING NARCOSIS.
CHRONIC:REPORTED/PROLONGED CONTACT DEFATTS SKIN, RESULTING IN DERMATITIS. EYE:IRRITATION.
ACUTE:DIRECT CONTACT WITH LIQUID MAY RESULT IN IRRITATION, REDNESS, TEARING, &
PAIN. VAPORS MAY CAUSE IRRITATION. CHRONIC: REPORTED/PROLONGED CONTACT MAY CAUSE
CONJUNCTIVITIS. INGESTION:IRRITANT OR NARCOTIC. ACUTE: NUMBNESS, IRRITATION OF
GI TRACT, NAUSEA, VOMITING,(ING 7)
Medical Conditions Aggravated by Exposure:
NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures =====
=====

First Aid:INHALATION:REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS
STOPPED, GIVE ARTIFICIAL RESPIRATION. MAINTAIN AIRWAY & BLOOD PRESSURE & ADMINISTER O₂
IF AVAILABLE. KEEP AFFECTED PERSON WARM & AT REST. ADMINISTRATION OF O₂ SHOULD BE
PERFORMED BY QUALIFIED PERSONNEL. GET MEDICAL ATTENTION IMMEDIATELY. SKIN:REMOVE
CONTAMINATED CLOTHING & SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP/MILD
DETERGENT & LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE

NCE OF CHEM REMAINS
(ING 8)

===== Fire Fighting Measures =====

Flash Point:-7F,-22C

Lower Limits:1.1%

Upper Limits:7.5%

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR FOAM.
FOR LARGE FIRES, USE WATER SPRAY, FOG OR ALCOHOL FOAM.

Fire Fighting Procedures:MOVE CNTNR FROM FIRE AREA IF POSS. COOL
FIRE-EXPOSED CNTNRS W/WATER FROM SIDE UNTIL WELL AFTER FIRE IS OUT.
FOR MASSIVE FIRE IN STORAGE AREA, USE (SUPP DATA)

Unusual Fire/Explo

sion Hazard:DANGER FIRE/SEVERE EXPLOSION HAZ WHEN
EXPOSED TO HEAT/FLAME. VAPORS ARE HVR/AIR & MAY TRAVEL A
CONSIDERABLE DISTANCE TO A SOURCE OF IGNIT & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF IGNIT SOURCES. STOP LEAK IF YOU CAN
DO IT WITHOUT RISK. USE WATER SPRAY TO REMOVE VAPS. FOR SML SPILLS,
TAKE UP WITH SAND/OTHER ABSORBENT MATL & PLACE INTO CNTNRS FOR
LATER DISP. FOR LRG SPIL LS, DIKE AS CLOSE TO
THE SPILL AS IS (ING
11)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD: EXPOSURE LIMT TO 1000
PPM:SUPPLIED-AIR RESP SELF-CONTAINED BRTHG APPARATUS. 5000
PPM:SELF-CONTAINED BRTHG APPARATU

S W/A FULL FACEPIECE OPERATED IN
PRESS-DEMAND OR OTHER POSITIVE PRE SS MODE, OR USE EQUIVALENT
RESP.(ING 13)

Ventilation:PROVIDE LOC EXHST VENT/GEN DILUTION VENT TO MEET
PERMISSIBLE EXPOSURE LIMITS. VENT EQUIPMENT MUST BE EXPLOSION
PROOF.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEM WORK GOGG/FULL LENGTH FSHLD .

Other Protective Equipment:EMPLOYER SHALL PROVIDE EYE-WASH FOUNTAIN
WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE. EMPLOYEE SHALL
WEAR (ING 16)

Wo

rk Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC:UNMANNED HOSE HOLDER/MONITOR NOZZ, ELSE WITHDRAW FROM AREA & LET FIRE BURN. WITHDRAW IMMED IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICE/ANY DISCOLORATION OF STORAGE TANK DUE TO FIRE. EXTING ONLY IF FLOW CAN BE STOPPED; USE WATER IN FLOODING AMTS AS FOG SOLID STREAMS MAY NOT BE EFFECTIVE. (ING 2)

===== Physical/Chemical Properties =====

Boiling

Pt:B.P. Text:136F,58C

Melt/Freeze Pt:M.P/F.P Text:-139F,-95C

Vapor Pres:124 @ 20C

Vapor Density:3.0

Spec Gravity:0.7

Solubility in Water:INSOLUBLE

Appearance and Odor:COLORLESS LIQUID, FAINT ODOR, VERY VOLATILE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS: VIOLENT REACTION. DINITROGEN TETRAOXIDE: POSSIBLE EXPLOSION.

Stability Condition to Avoid:MAY BE IGNITED BY HEAT, SPARKS, OR FLAMES.

VAPS ARE HVR/AIR

& MAY TRAVEL TO A SOURCE OF IGNIT & FLASH BACK.

(ING 5)

Hazardous Decomposition Products:COMBUSTION MAY RELEASE ACRID SMOKE AND IRRITATING FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States

of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.