

CROSSFIELD PRODUCTS CORP -- DEX-O-TEX STANDARD GROUT POWDER,PART A --
5610-00-852-1901

===== Product Identification =====

Product ID:DEX-O-TEX STANDARD GROUT POWDER,PART A

MSDS Date:01/01/1987

FSC:5610

NIIN:00-852-1901

MSDS Number: BQWLT

=== Responsible Party ===

Company Name:CROSSFIELD PRODUCTS CORP

Address:3000 E. HARCOURT ST

City:COMPTON

State:CA

ZIP:90221-5504

Country:US

Info Phone Num:213-636

-0561

Emergency Phone Num:213-636-0561

CAGE:60782

=== Contractor Identification ===

Company Name:CROSSFIELD PRODUCTS CORP.

Address:3000 EAST HARCOURT ST.

Box:City:COMPTON

State:CA

ZIP:90221

Country:US

Phone:310-886-9100

CAGE:60782

===== Composition/Information on Ingredients =====

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

===== Hazards Ident

ification =====

LD50 LC50 Mixture:ACGIH-TLV TWA=0.1MG/M3 SI-O2
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:POSSIBLE IRRITANT.SKIN:POSSIBLE
IRRITANT.INHAL:MAY CAUSE DELAYED LUNG DAMAGE.
Explanation of Carcinogenicity:SI-O2 HAS BEEN INVESTIGATED BY RTECS
92-4 AS A TUMORIGEN.
Effects of Overexposure:INHAL:DELAYED LUNG DAMAGE.
Medical Cond Aggravated by Exposure:PERSONS WITH
H KNOWN RESPIRATORY
AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR.EYES:FLUSH WITH WATER FOR 15
MINUTES.SKIN:WASH WITH SOAP AND WATER.INGEST:SEEK QUALIFIED MEDICAL
HELP.

===== Fire Fighting Measures =====

Extinguishing Media:NOT A FIRE HAZARD.
Fire Fighting Procedures:NO SPECIAL REQUIREMENTS.
Unusual Fire/Explosion Hazard:NONE

=====

=== Accidental Release Measures =====

Spill Release Procedures:USE DUSTLESS COLLECTION(WET SWEEPING,HEPA
VACUUMING);PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY AREA.USE DUSTLESS SYSTEMS
FOR HANDLING,STORAGE AND CLEAN-UP.
Other Precautions:PRODUCT WILL HARDEN IF IN CONTACT WITH WATER.

===== Exposure Controls/Personal Prot

ection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR IF DUST
LEVELS EXCEED 0.1MG/M3.
Ventilation:LOCAL EXHAUST OR GENERAL(MECHANICAL).FOLLOW OSHA STANDARDS.
Protective Gloves:OPTIONAL.
Eye Protection:GOGGLES
Other Protective Equipment:CLOTHING TO PROTECT SKIN
Work Hygienic Practices:PRACTICE GOOD HOUSEKEEPING WHERE THIS MATERIEL
IS USED.
Supplemental Safety and Health
KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1
Boil
ing Pt:B.P. Text:N/R(SOLID)
Spec Gravity:2.65
Solubility in Water:NEGLIGIBLE
Appearance and Odor:POWDER,GRANULAR;NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
HYDROFLUORIC ACID(EVOLVES SI-F4 GAS).
Stability Condition to Avoid:CONTAMINATION BY WATER.
Hazardous Decomposition Products:MANUFACTURER STATES NONE.
Conditions to Avoid Polymerization:WATER,FORMS HYDRATE.

===== Disposal Considerations =====
=====

Waste Disposal Methods:DISPOSE OF IN SANITARY LANDFILL IN ACCORDANCE W/
FEDERAL,STATE & LOCAL REGULATIONS ON SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should see

k competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.