

HEFLIN STEEL COMPANY -- ALUMINUM ALLOYS -- 3439-00-178-8590

=====
Product Identification
=====

Product ID:ALUMINUM ALLOYS

MSDS Date:05/11/1987

FSC:3439

NIIN:00-178-8590

MSDS Number: BQXRT

=== Responsible Party ===

Company Name:HEFLIN STEEL COMPANY

Address:1111 W MARICOPA FREEWAY

Box:1249

City:PHOENIX

State:AZ

ZIP:85001

Country:US

Info Phone Num:602-252-8061

Emergency Phone Num:602-252-8061

CAGE:9J

432

=== Contractor Identification ===

Company Name:HEFLIN STEEL COMPANY

Address:1111 W MARICOPA FREEWAY

Box:1249

City:PHOENIX

State:AZ

ZIP:85001

Country:US

Phone:602-252-8061

CAGE:9J432

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 90-99.7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name:COBALT (SARA III)

CAS:7440-48-4

RTECS #:GF87500

00

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1 MG/M3;AS CO

ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2MG/M3 FUME; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:IRON OXIDE (FE2O3)

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE

),B2; 9293

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.2-0.7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:MAGNESIUM OXIDE

CAS:1309-48-4

RTECS #:OM3850000

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 PARTICULATE

ACGIH TLV:10 MG/M3;TDUST; 9293

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 1-10%

Other

REC Limits:NONE RECOMMENDED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMEN
DED
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR WELDING FUMES IS 5 MG/M3
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: COPPER FUMES MAY CAUSE UPPER
RESPIRATORY TRACT IRRITATION, NAUSEA, AND METAL FUME FEVER.
CHRONIC: LEAD FUMES MAY CAUSE CENTRAL NERVOUS SYSTEM DISTURBANCES,
RENAL CHANGES, PERIPHERAL NEUROPATHY, GASTROINTESTINAL
DISTURBANCES, ANEMIA,AND CHROMOSOMAL CHANGES.
Explanation of Carcinogenicity:NICKEL AND CHROMIUM IF PRESENT WILL BE
ONLY IN TRACE AMOUNTS.
Effects of Overexposure:UPPER RESPIRATORY TRACT IRRITATION, NAUSEA,
METAL FUME FEVER.
Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY DISEASES
MAY BE AGGRAVATED BY EXPOSURE TO THE DUST AND FUMES OF THIS
PRODUCT.

===== First Aid Measures =====

=====

First Aid:INHALATION: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF NOT BREATHING, GIVE CPR. IF NO DETECTABLE PULSE, GIVE HEART MASSAGE. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INGESTION: SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE CLASS D DRY POWDER EXTINGUISHING MATERIAL. DO NOT USE WATER OR HALOGEN ON DUST FIRES

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DUST MAY IGNITE READILY. DAMP ALUMINUM DUST MAY HEAT SPONTANEOUSLY WITH LIBERATION OF HYDROGEN TO FORM EXPLOSIVE AIR MIXTURES.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DISPOSAL CONTAINER. AVOID INHALATION AND SKIN EXPOSURE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH, ARM PROTECTOR, APRON, HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE MEASURES

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING, SMO

KING OR
USING SANITARY FACILITIES.
Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:N1
Melt/Freeze Pt:M.P/F.P Text:900F,482C
Spec Gravity:2.5-2.9
Solubility in Water:INSOLUBLE
Appearance and Odor:SOLID WITH SILVER METALLIC LUSTRE. ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
REACTS WITH STRONG ACIDS AND SODIUM HYDROXIDE. AVOID BROMATES, IODATES,
AMM
ONIUM NITRATE AND STRONG OXIDIZERS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:FUMES OF METALS AND METAL OXIDES FROM
ELECTRODE AND BASE METAL, CARBON MONOXIDE, CARBON DIOXIDE, OZONE,
NITROGEN OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL OFFICER.
DISPOSE OF FUMES, FLUX OR WELD GRINDING RESIDUE FROM THE WORK AREA
IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONME
NTAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to th
eir
particular situation.