

COURTAULDS AEROSPACE, INC. -- PR-1436-G SPRAYABLE, PART B -- 8030-00-008-7204

=====  
Product Identification  
=====

Product ID:PR-1436-G SPRAYABLE, PART B

MSDS Date:07/24/1991

FSC:8030

NIIN:00-008-7204

Kit Part:Y

MSDS Number: BQXZQ

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-2

40-2060

Emergency Phone Num:800-228-5635/800-424-9300(CHEMTREC)

Preparer's Name:AS/LPM

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5%

Other REC Limits:NONE

SPECIFIED  
OSHA PEL:200 PPM/STEL 300 PPM  
ACGIH TLV:200 PPM/STEL 300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:HYDROGENATED TERPHENYLS  
CAS:61788-32-7  
Fraction by Wt: 25%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.5 PPM  
ACGIH TLV:0.5 PPM

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:  
XR2275000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PHENOL POLYMER WITH FORMALDEHYDE (PHENOLIC RESIN)  
CAS:28470-78-2  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:4,4 ISOPROPYLIDENE DIPHENOL EPICLOROHYDRIN RESIN  
CAS:25036-25-3  
Fr

action by Wt: < 5%  
Other REC Limits:NONE SPECIFIED

Ingred Name:MAGNESIUM CHROMATE  
CAS:13423-61-5  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:.05MG/M3,STEL 1MG/M3  
ACGIH TLV:0.05 MG/M3

Ingred Name:ALUMINUM  
CAS:7429-90-5  
RTECS #:BD0330000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10MG/M3  
ACGIH TLV:10MG/M3 TDUST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogeni

city:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: LOCAL

IRRITATION. MAY CASUE ALLERGIC SKIN RASH IN SENSITIZED INDIVIDUALS.

INHALATION: IRRITATION TO NOSE & THROAT. PRO/EXPO ABOVE PEL CAUSE

HEADACHE, FATIGUE, CONFUSION, DIZZIN ESS, DROWSINESS, NUMBNESS,

UNCONSCIOUSNESS. PRO/EXPO LIVER/KIDNEY DAMAGE. INGESTION: NAUSEA,

VOMITING,LIVER/KIDNEY DAMA.

Effects of Overexposure:SKIN: PROLONGED EXPOSURE TO HEXAVALENT CHROMIUM  
COMPOUNDS OVER THE

PEL MAY CAUSE PAINLESS PENETRATING ULCERS OF THE

SKIN. INHALATION: PROLONGED EXPOSURE TO HEXAVALENT CHROMIUM

COMPOUNDS OVER THE PEL M AY CAUSE PENETRATING ULCERS OF THE MUCOUS

MEMBRANES OF THE NOSE & PERFORATION OF THE CARTILAGINOUS NASAL

SEPTUM.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES, IF SYMPTOMS  
PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP & WATER. IF  
SYMPTOMS PERSIST, CONSU

LT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:28.0F,-2.2C  
Lower Limits:1.8  
Upper Limits:10.0% (MEK)  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.  
Fire Fighting Procedures:USE COMPLETE PERSONAL PROTECTION. USE WATER TO COOL HEAT EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:PROTECT FROM IGNITION. WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBENT MATERIAL AND SCOOP INTO CONTAINER. CLEAN RESIDUE WITH 1,1,1-TRICHLOROETHANE.

===== Handling and Storage =====

Handling and Storage Precautions:THIS PRODUCT CONTAINS TOXIC CHEMICAL(S) SUBJECT TO REPORT. REQUIRE.OF SECTION 313 OF TITLE III OF SUPERFUND AMEND. & REAUTHOR.ACT 1986 40 CFR PART 372

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING, APPLYING IN CONFINED AREAS OR IN OTHER CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVELS OF SOLVENT IN EXCESS OF PEL, USE ORGANIC VAPOR CARTRIDGE RESPIRATOR OR AIR-SUPPLIED RESPIRATOR.  
Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.  
Protective Gloves:SOLVENT-RESISTANT GLOVES.  
Eye Protection:GOGGLES OR FULL FACE SHIELD.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3  
Spec Gravity:1.20  
Viscosity:80 POISE  
Solubility in Water:MODERATE  
Appearance and Odor:SILVER GRAY THIXOTROPIC PASTE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Hazardous Decomposition Products:OXIDES OF CARBON, SO2, TRACES OF H2S.

=====

===== Disposal Considerations =====

Waste Disposal Methods:D-001 AND D-007 D-035 EPA HAZARDOUS WASTE.  
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability  
for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.