

G C THORSEN -- SILVER PRINT -- 8030-00-711-2192

===== Product Identification =====

Product ID:SILVER PRINT
MSDS Date:06/28/1991
FSC:8030
NIIN:00-711-2192
MSDS Number: BQYGP
=== Responsible Party ===
Company Name:G C THORSEN
Address:1801 MORGAN STREET
City:ROCKFORD
State:IL
ZIP:61105
Country:US
Info Phone Num:815-968-9661
Emergency Phone Num:815-968-9661
Preparer's Name:V HAGEMAN
CAGE:THORS
=== Con
tractor Identification ===
Company Name:G C THORSEN
Address:1801 MORGAN STREET
City:ROCKFORD
State:IL
ZIP:61105
Country:US
Phone:815-968-9661
CAGE:THORS

===== Composition/Information on Ingredients =====

Ingred Name:SILVER POWDER (SARA III)
CAS:7440-22-4
RTECS #:VW3500000
Fraction by Wt: 42%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.01 MG/M3
ACGIH TLV:0.1 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by

Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/STEL 200 PPM
ACGIH TLV:150 PPM/STEL 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL METHACRYLATE (SARA III)
CAS:80-62-6
RTECS #:OZ5075000
Fraction by Wt: 33%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/STEL 125 PPM
ACGIH TLV:100 PPM/STEL 125 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 318 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====
=====

Health Hazards Acute and Chronic:EFFECTS OF OVEREXPOSURE:
CONJUNCTIVITIS, DERMATITIS, COUGH, REPIRATORY INFLAMMATION,
HEADACHE, ANOREXIA, NAUSEA, DROWSINESS, DECREASED BLOOD PRESSURE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER.
INHALATION: FRESH AIR, OXYGEN. INGESTION: GASTRIC LAVAGE--DO NOT
INDUCE VOMITING. CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:66.0F,18.9C
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:1.7
Upper Limits:15.0
Extinguishing Media:CO2, CHEMICAL FOAM
Fire Fighting Procedures:VENTILATE AREA WELL--USE SCBA--AVOID BREATHING
FUMES
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HIGH HEAT AND IGNITION
SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE WELL. PICK UP WITH AN INERT
ABSOR

BENT MATERIAL. STORE IN SEALED CONTAINERS

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT, IGNITION SOURCES
AND OXIDIZERS.

Other Precautions:VENTILATE STORAGE AREA WELL

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR OR SCBA.

Ventilation:LOCAL EXHAUST. MECHANICAL AS REQUIRED TO MEET TLV.

Protective Gloves:RUBBER GLOVES

Eye Protection:CHEMICAL

GOGGLES OR FACE SHIELD

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:248F,120C

Vapor Pres:7.8

Vapor Density:>1

Spec Gravity:1.27

Evaporation Rate & Reference:1

Solubility in Water:NOT

Appearance and Odor:GREY LIQUID--BUTYL ODOR

Percent Volatiles by Volume:28

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS

Stability Condition to Avoid:

HEAT OR IGNITION SOURCES

Hazardous Decomposition Products:ACRID SMOKE AND IRRITATING FUMES

===== Disposal Considerations =====

Waste Disposal Methods:LICENSED INCINERATOR

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.