

NATIONAL DRAEGER INC -- HARDENER T9539 -- 8040-01-247-9689

===== Product Identification =====

Product ID:HARDENER T9539

MSDS Date:09/01/1992

FSC:8040

NIIN:01-247-9689

MSDS Number: BQYMS

=== Responsible Party ===

Company Name:NATIONAL DRAEGER INC

Address:101 TECHNOLOGY DRIVE

City:PITTSBURGH

State:PA

ZIP:15275

Country:US

Info Phone Num:412-787-8389

Emergency Phone Num:800-424-9300 CHEMTREC

CAGE:5383

3

=== Contractor Identification ===

Company Name:NATIONAL DRAEGER INC

Address:101 TECHNOLOGY DRIVE

Box:City:PITTSBURGH

State:PA

ZIP:15372

Country:US

Phone:412-787-8383 OR 412-787-8389

CAGE:53833

===== Composition/Information on Ingredients =====

Ingred Name:TRIS (4-ISOCYANATOPHENYL) THIOPHOSPHATE (TT)

CAS:4151-51-3

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

Ingred Name:METHYLENE CHLORIDE (MC) (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 74-79.5%

Other R

EC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MONOCHLOROBENZENE (MCB) (SARA III)
CAS:108-90-7
RTECS #:CZ0175000
Fraction by Wt: 0.5-3.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:75 PPM
ACGIH TLV:75 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Hea

lth Hazards Acute and Chronic:NONE UNDER NORMAL CONDITIONS.
INHAL:IRRITANT, NARCOTIC & NEUROTOXIN. SKIN:IRRITANT. IRRIT,
SCALING, CRACKING, REDDENING, SWELLING, RASH, BLISTERING. CURED
MAT'L DIFFICULT TO REMOVE. EYE:IRRITANT, TEAR ING, REDDENING,
SWELLING. INGEST:IRRIT,INTERNAL CORROSIVE ACTION (SORE THROAT,
ABDOM PAIN, NAUSEA, VOMITING, DIARRHEA.

Explanation of Carcinogenicity:MC CLASSIFIED AS ANTICIPATED HUMAN
CARCINOGEN BY NTP. MC IS LISTED IN VOL 41 AS CATEGORY 2B (IA
RC).

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE
ARTIF RESP. GET MED AID IMMED. SKIN:REMOVE CONTAM CLOTH IMMED. WASH
AREA W/SOAP OR MILD DETERGNT & LRG AMT WATER. GET MED AID IMMED.
EYE:WASH E YES IMMED W/LRG AMT WATER OR NORMAL SALINE, LIFTING
EYELIDS. GET MED AID IMMED. INGEST:PREVENT ASPIRATION. MAINTAIN
AIRWAY, BP, RESPRTN. GET MED AID IMMED. QUALIFIED MED PERSONNEL
MUST GIVE

TREATMENT.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:DRY CHEMICAL; CARBON DIOXIDE, FOAM, WATER
Fire Fighting Procedures:COOL FIRE EXPOSED CONTAINERS WITH WATER WATER
SPRAY.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH INERT ABSORBENT AND PLACE IN
CONTAINER FOR LATER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED AND AWAY
FROM HEAT AND IGNITION SOURCES, AND DO NOT SMOKE.
Other Precautions:WATER POLLUTING LIQUID. THE MATERIAL MUST NOT FLOW
INTO WASTE WATER OR SURFACE WATERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUPPLIED AIR RESPIRATOR OR SELF-CONTAINED
BREATHING APPARATUS.
Ventilation:PROVIDE LOCAL EXHAUST. SHOULD BE USED TO MAINTAIN LEVELS
BELOW EXPOSURE LIMITS OR GUIDELINES.
Protective Gloves:CHEMICAL RESISTANT GLOVES
Eye Protection:GOGGLES RECOMM WHEN CONTACT POSSIBLE
Other Protective Equipment:CHEM RESISTANT CLOTHING RECOMMENDED WHEN
PHYSICAL CONTACT POSSIBLE. SAFETY SHOWER & EYEWASH STATION SHOULD
BE AVAILABLE.
Work Hygienic Practices:A SAFETY SHOWER AND EYEWASH STATION SHOULD BE
AVAILABLE. IN EVENT CONCENTRATIONS MEET/EXCEED TLVS, USE RESP
PROTECTION.
Supplemental Safety and Health

===== Physical/Chemical P

properties =====

HCC:T4

Spec Gravity:1.32 G/CM3 @23C

Evaporation Rate & Reference:80 (BU AC=1)

Solubility in Water:REACT SLOWLY W/WATER

Appearance and Odor:YELLOWISH LIQUID TO BROWNISH LIQUID WITH ODOR OF SOLVENTS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER,AMINES,ALCOHOL,ACID,& ALKALI.MC REACTS VIOLENTLY W/UNPROTECTED ALUMINUM & ZINC SURFACES,SODIUM,POTSSIUM,MAGNESIUM.

Stability Condition to Av

oid:AVOID TEMPERATURES ABOVE 40C., OPEN FLAMES

AND WELDING AREAS WHICH CAN CAUSE THERMAL DEGRADATION.

Hazardous Decomposition Products:BY HIGH HEAT & FIRE: CO, NOX, POX, SOX, HCL AND SMALL AMOUNTS OF PHOSGENE AND CHLORINE.

Conditions to Avoid Polymerization:AVOID TEMPERATURES ABOVE 40C.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE. CONTACT LICENSED

CHEMICAL WASTE DISPOSAL AGENCY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.