

BAKER SEALANTS AND COATINGS CO -- ADHESIVE FOR ACCOUSTICAL MATERIALS --
8040-00-656-0929

===== Product Identification =====

Product ID:ADHESIVE FOR ACCOUSTICAL MATERIALS
MSDS Date:03/08/1990
FSC:8040
NIIN:00-656-0929
MSDS Number: BRFPK
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:B
City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Info Phone Number:201-333-6986 / FAX 201-333-6955
Emergency Phone Num:201-333-6986
Preparer's Name:CHARLES FRIEDMAN
CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6501
CAGE:33150

===== Composition/Information on Ingredients =====

===

Ingred Name:PRINCE CLAY
CAS:8031-18-3
Other REC Limits:NONE SPECIFIED

Ingred Name:ROSIN CUT T
CAS:514-10-3
RTECS #:TP8580000
Other REC Limits:NONE SPECIFIED

Ingred Name:TOLREZ
CAS:8016-81-7
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Other REC Limits:NONE SPECIFIED

Ingred Name:QUICKLIME
CAS:1305-78-8
RTECS #:EW3100000
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes o
f Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CAN CAUSE IRRITATION, REDNESS,
TEARING. SKIN: PROLONGED AND REPEATED CONTACT CAN CAUSE MODERATE
IRRITATION. INHALATION: EXCESSIVE INHALATION OF VAPORS MAY CAUSE
NASAL AND RESPIRATORY IRRITATION. INGESTION: CAN CAUSE
GASTROINTESTINAL IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER
FOR 15 MINUTES. SKIN: WASH WITH SOAP
AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK WATER
AND INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:140F,60C
Lower Limits:2.0
Upper Limits:12
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL----TRANSFER INTO
CONTAINERS.

=====
===== Handling and Storage =====

=====

Handling and Storage Precautions:NORMAL PRECUTIONS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY

Ventilation:LOCAL

Protective Gloves:RUBBER

Eye Protection:PROTECTIVE GOGGLES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:180F,82C

Vapor Pres:33

Vapor Density:2.0

Spec Gravity:1.366 (WATER=1)

pH:7.0

Evaporation Rate & Reference:1.4 (BU AC
=1)

Solubility in Water:COMPLETE

Appearance and Odor:BROWNISH SEMI SOLID CHARACTERISTIC ODOR

Percent Volatiles by Volume:5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods:AS PER LOCAL, STATE OR FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.