

DEFT INC -- CAT, MIL-C-85285B, 12197, P/C 040R001CAT -- 8010-01-329-6298

=====
Product Identification
=====

Product ID:CAT, MIL-C-85285B, 12197, P/C 040R001CAT

MSDS Date:02/24/1993

FSC:8010

NIIN:01-329-6298

Kit Part:Y

MSDS Number: BRKMN

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVENUE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergency Ph

one Num:714-474-0400 800-424-9300(CHEMTREC)

Preparer's Name:NORM GAUL

CAGE:33458

=== Contractor Identification ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:800 424-9300

CAGE:33458

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC ISOCYANATE HEXAMETHYLENE DIISOCYANATE

(HDI)
CAS:28182-81-2
RTECS #:HQ9170000
Fraction by Wt: 55%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:0.005 TWA C 0.02

Ingred Name:AROMATIC HYDROCARBONS (MIXTURE OF C8'S TO C10'S) (VAPOR
PRESSURE 3 MM HG @ 68F)

CAS:64742-95-6
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM

Ingred Name:N-BUTYL ACETATE (VAPOR PRESSURE 13 MM HG @ 68F)

CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/STEL 200 PPM
ACGIH TLV:150 PPM/STEL 20
0 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL-3-ETHOXYPROPIONATE (VAPOR PRESSURE .7 MM HG @ 68F)

CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: < 0.1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:STEL 100 PPM
ACGIH TLV:50 PPM - TWA

Ingred Name:METHYL N-PROPYL KETONE (VAPOR PRESSURE 27.8 MM HG @ 68F)

CAS:107-87-9
RTECS #:SA7875000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/STEL 250 PPM
ACGIH TLV:200 PPM/STEL 250 PPM

Ingred Name:VOC: 438 G/L

RTECS #:999

9999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INGESTION: CAN RESULT IN
IRRITATION & POSSIBLE CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE
& DIGESTIVE TRACT. VOMITING MAY CAUSE ASPIRATION OF THE SOLVENT
RESULTING IN CHEMICAL PNEUMONITIS. VAPORS ARE IRRITATING TO EYES,
NOSE & THROAT. INHALED CAUSE HEADACHES, DIFFICULT BREATHING & LOSS
OF CONSCIOUSNESS.

Effects of Overexposure:INHALATION: IRRITATION RESPIRATORY TRACT.
HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION,
UNCONSCIOUSNESS/COMA. SKIN: IRRITATION. SWELLING, REDNESS, RASH.
EYES: LIQUID, AEROSOLS, VAPORS IRRITATING CAUSE TEARING, REDNESS,
SWELLING, STINGING. SKIN ABSORP: CAUSE MODERATE IRRITATION,
DRYING/CRACKING DUE TO DEFATTING ACTION

Medical Cond Aggravated by Exposure:ASTHMA AND
ANY OTHER RESPIRATORY
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE
SENSITIZATION. NERVOUS SYSTEM DEPRESSION.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET
MEDICAL ATTENTION. SKIN: WASH AFFECTED AREAS WITH SOAP & WATER.
EYES: FLUSH WITH CLEAN LUKEWARM WATER (LOW PRESSURE) FOR AT LEAST
15 MINUTES , OCCASIONALLY LIFTING EYELIDS. GET MEDICAL ATTENTION.
INGESTION:
DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN
UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:46.0F,7.8C
Lower Limits:1.00 %
Upper Limits:8.00 %
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:FIREFIGHTING EQUIPMENT W/SCBA. H2O USED COOL
CLOSED CONTAINERS PREVENT PRESSURE BUILDUP/AUTO IGNITION/EXPLOSION.
DURING FIRE HDI VAPORS GENERA

TED BY COMBUSTION.

Unusual Fire/Explosion Hazard: ISOLATE FROM ALL HEAT TYPES. CLOSED CONTAINERS EXPLODES EXPOSED TO EXTREME HEAT. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMP. PRODUCTS CAUSE HEALTH HAZARD

===== Accidental Release Measures =====

Spill Release Procedures: EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions: BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106 AVOID STORING NEAR HIGH TEMPERATURES. STORE IN TIGHTLY CLOSED CONTAINERS. STORE IN WELL VENTILATED AREAS.

Other Precautions: PREVENT LEAKAGE. PREVENT BREATHING VAPORS, SPRAY MISTS. OVEREXPO CAUSE ALLERGIC REACTIONS. AVOID CONTACT WITH SKIN, & EYES. DON'T INGEST. DON'T HANDLE UNTIL THE MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ & UNDERSTOOD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE. VENT AREA TO KEEP EXPOSURE LEVELS BELOW THE OSHA PERMISSIBLE LIMITS. AIR SUPPLIED RESPIRATOR IS RECOMMENDED. VAPOR PARTICULATE RESPIRATOR (TC23C NIOSH/MSHA) APPROPRIATE WHEN 10 TIMES BELOW LIMIT.

Ventilation: EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS OF SOLVENT, HDI & POLYISOCYANATES BELOW RESPECTIVE TLV'S.

Protective Gloves: COTTON, NEOPRENE, RUBBER, POLYETHYLENE

Eye Protection: CHEMICAL GOGGLES, FULL-FACE SHIELD

Other Protective Equipment: THE USE OF LONG SLEEVE & LONG LEG CLOTHING IS RECOMMENDED. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM. SMOKE IN DESIGNATED AREAS ONLY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text:

213 TO 338F

Vapor Density:> AIR

Spec Gravity:1.0036

Evaporation Rate & Reference:1.23 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:51.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIAL WHICH REA

CT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT IN CINE RATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.