

RADIATOR SPECIALTY COMPANY -- TITE SEAL GASKET AND JOINT SEALING COMPOUND --
8030-00-065-1970

===== Product Identification =====

Product ID:TITE SEAL GASKET AND JOINT SEALING COMPOUND

MSDS Date:07/01/1992

FSC:8030

NIIN:00-065-1970

MSDS Number: BRLWQ

=== Responsible Party ===

Company Name:RADIATOR SPECIALTY COMPANY

Address:1400 W. INDEPENDENCE BLVD.

City:CHARLOTTE

State:NC

ZIP:28208

Info Phone Num:

704-377-6555

Emergency Phone Num:704-377-6555

Preparer's Name:T. LIEBMAN

CAGE:77628

=== Contractor Identification ===

Company Name:RADIATOR SPECIALTY COMPANY

Address:1900 WILKINSON BLVD.

Box:34689

City:CHARLOTTE

State:NC

ZIP:28208

Country:US

Phone:704-377-6555/303-623-5716

CAGE:77628

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

LD50 LC50 Mixtu

re:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITANT, MAY CAUSE CORNEAL DAMAGE. SKIN CONTACT: SKIN IRRITANT ON PROLONGED EXPOSURE. INHALATION: ALCOHOL FUMES MAY CAUSE HEADACHE AND IRRITATION. INGESTION: HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:THIS PRODUCT DOES NOT CONTAIN MORE THAN .1% OF ANY KNOWN CARCINOGEN LISTED BY NTP, IARC, OR OSHA.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH EYE WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH WITH SOAP AND WATER. INHALATION: MOVE TO FRESH AIR. IF NEEDED GIVE ARTIFICIAL RESPIRATION. INGESTION: INDUCE VOMITING, DRINK 2 GLASSES OF MILK, CONSULT A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:60.0F,15.6C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF-CONTAINED, POSITIVE PRESSURE BREATHING APPARATUS AND PROTECTIVE CLOTHES.

Unusual Fire/Explosion Hazard:MAY PRODUCE DENSE SMOKE

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONFINE SPILL, REMOVE IGNITION SOURCES, VENTILATE AREA, WIPE AND SCRAPE UP WITH RAGS, TRANSFER TO WASTE DRUM.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES AND OXIDIZING AGENTS.

Other Precautions:KEEP AWAY FROM CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:N/A FOR CONSUMER. IF TLV IS EXCEEDED, WEAR RESPIRATOR FOR BULK HANDLING.

Ventilation:USE WITH ADEQUATE GENERAL VENTILATION

P

rotective Gloves:RUBBER (BULK HANDLING)
Eye Protection:GOGGLES (BULK HANDLING)
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
PARTS NUMBER LISTED BY THE MANUFACTURER INCLUDE: T2-01, T2-03, T2-03V,
T2-11.

===== Physical/Chemical Properties =====

HCC:F3
Spec Gravity:1.5
pH:7
Solubility in Water:SLIGHT
Appearance and Odor:BLACK PASTE WITH ALCOHOLIC ODOR
Percent Volatiles by Volume:15

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:SMOKE, CARBON OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICIABLE
GOVERNMENT LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.