

COLORADO PAINT COMPANY -- WHITE STENCIL PAINT 1100 -- 8010-00-285-4933

=====
Product Identification
=====

Product ID:WHITE STENCIL PAINT 1100

MSDS Date:03/10/1992

FSC:8010

NIIN:00-285-4933

MSDS Number: BRNKW

=== Responsible Party ===

Company Name:COLORADO PAINT COMPANY

Address:4747 HOLLY STREET

City:DENVER

State:CO

ZIP:80216

Country:US

Info Phone Num:303-388-9265

Emergency Phone Num:303-388-9265 8

00-424-9300(CHEMTREC)

Preparer's Name:CHRISTOPHER M. COOK

CAGE:25449

=== Contractor Identification ===

Company Name:COLORADO PAINT CO

Address:4747 HOLLY STREET

Box:City:DENVER

State:CO

ZIP:80216-6409

Country:US

Phone:303-338-9265

CAGE:25449

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE (SARA 313) (VAPOR PRESSURE 5.1 MM HG @ 68F)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.39%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA

Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC PETROLEM DISTILLATES (VAPOR PRSSURE 0.4 MM HG @ 100F)

CAS:64742-89-8
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0.46%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA 313) (VAPOR PRESSURE 22.0 MM HG @ 68F)

CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 0.49%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC HYDROCARBON/MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG @ 68F)

CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 0.42%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:VOC: 3.02 LB/GL; 362 G/L

RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Id

entification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:YES

Health Hazards Acute and Chronic:ACUTE: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA. ASPIRATIONS OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC: REPEATED EXPOSURE TO HIGH CONCENTRATIONS MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM & PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL

& RESPIRATORY IRRITATION, CNS EFFECTS INCLUDE DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS & EVEN DEATH. EYE & SKIN: SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. REPEATED/PROLONGED CONTACT CAUSE DEFATTING OR DERMATITIS.

Medical Cond Aggravated by Exposure:POSSIBLE ALLERGIC REACTIONS.

INTENTIONAL MISUSE OR DELIBERATELY CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF FRESH WARM WATER, OPENING EYES OCCASIONALLY, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION &/OR OXYGEN IF NECESSARY & GET MEDICAL ATTENTION. KEEP INDIVIDUAL WARM & QUIET. INGESTION: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:50.0F,10.0C

Lower

Limits:0.9 %

Upper Limits:7.0 %

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR TRAVEL ALONG GROUND, OR BY VENTS & IGNITED BY HEAT, PILOT LIGHTS OTHER FLAMES & IGNITION SOURCES DISTANT FROM MATERIAL HANDLING POINT.

===== Accidental Release Measures =====

=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. DIKE AREA & ABSORB MATERIAL WITH VERMICULITE OR OTHER ABSORBENT, OR PUMP MATERIAL INTO TANK FOR REUSE OR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM ALL HEAT TYPES. DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BLDGS DESIGNED FOR STORAGE OF NFPA CLASS IB FLAMMABLE LIQUIDS.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN

EMPTY, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPORS, LIQUID, &/OR SOLIDS), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED . NEVER CUT, WELD, TORCH ON OR NEAR DRUM

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOLSURE LIMITS ARE EXCEEDED OR IF APPLIED BY SPRAYING, USE APPROPRIATE, PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR, REFER TO OSHA 29 CFR 1910-134 "RESPIRATOR PROTECTION.

Ventilation:PROVIDE SUFFICIENT MECHANICAL VENTILATION (GENERAL &/OR LOCAL EXHAUST) TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NITRILE, RUBBER OR NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED CONTACT WITH SKIN, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

=====

HCC:F2

Boiling Pt:B.P. Text:240 TO 285F

Vapor Density:> AIR

Spec Gravity:1.4

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:SMOOTH PAINT MATERIAL, SLIGHT SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES & FIRES.

Hazardous Decomposition Products:MAY FORM TOXIC

MATERIALS: CARBON
DIOXIDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE &
FEDERAL REGULATIONS. CONTACT LOCAL CHEMICAL WASTE COMPANY FOR
FURTHER INFORMATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
express

ly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.