

CON-LUX COATINGS, INC. -- INTERIOR LATEX FLAT GREEN 34558 -- 8010-00-598-5738
===== Product Identification =====

Product ID:INTERIOR LATEX FLAT GREEN 34558

MSDS Date:04/01/1993

FSC:8010

NIIN:00-598-5738

MSDS Number: BRNMQ

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emerge

ncy Phone Num:201-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE (AS NUISANCE DUST) (VAPOR PRESSURE 0.0 MM
HG @ 20C)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: >1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 T

DUST; 9293

Ingred Name:ALUMINUM SILICATE (KAOLIN) (AS NUISANCE DUST) (VAPOR PRESSURE 0.0 MM HG @ 20)
CAS:66402-68-4
Fraction by Wt: >1%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:10 MG/M3

Ingred Name:DIATOMACEOUS SILICA (AS NUISANCE DUST) (VAPOR PRESSURE 0.0 MM HG @ 20C)
CAS:61790-53-2
RTECS #:HL8600000
Fraction by Wt: >1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:20 MPPCF
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: >1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE RESPIRATN IF NEEDED. TREAT SYMPTOMATICALLY. EYE: FLUSH IMMED W/WATER 15 MIN. SEE DR. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHING. SEE DR, IF IRRITATION P ERSISTS. INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMIT. IF VOMITING OCCURS, KEEP HEAD AT/OR BELOW KNEE LEVEL
TO PREVENT ASPIRATION INTO LUNGS. SEE DR/POISON CONTROL CENTER IMMED.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:NONE REQUIRED
Fire Fighting Procedures:WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINER IN VICINITY.
Unusual Fire/Explosion Hazard:NONE REQUIRED

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE PERSONAL PROTECTION

EQUIPMENT AND APPROVED RESPIRATOR.

PREVENT MATERIAL FROM CONTACTING ANY WATER SOURCES OR SEWER LEADING TO SURFACE WATERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COMPLIANCE WITH GOOD HOUSEKEEPING PROCEDURES. PROTECT FROM FREEZING, STORE AT ROOM TEMPERATURE ABOVE 45F.

Other Precautions:GROUND CONTAINERS WHEN POURING LIQUIDS AND POWDERS TO AVOID STATIC CHARGE BUILD UP. DO NOT HANDLE UNTIL MANUFACTURERS

VENTILATION OR RESPIRATORY PROTECTION TO REMOVE DECOMPOSITION PRODUCTS DURING WELD ING OR FLAME CUTTING COATED SURFACES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR/OPEN AREAS, WHERE SUFFICIENT VENT EXISTS, RESPIRATOR GENERALLY NOT REQUIRED. IN RESTRICTED VENT AREAS, NIOSH/MSHA ORGANIC VAPOR RESPIRATOR RECOMMENDED. DURING SPRAY, RESPIRATOR W/ORGANIC VA POR & SPRAY MIST PROTECTION RECOMMENDED.

Ventilation:CONFINED SPA
CES MECHANICAL VENT REQUIRED TO KEEP AIR
CONTAMINANT CONCENTRATION BELOW PEL.

Protective Gloves:IMPERVIOUS TYPE REQUIRED FOR LONG/REPEAT

Eye Protection:SAFETY EYE WEAR--PROTECT AGAINST SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING
WASHROOM FACILITIES.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.

P. Text:212 TO 490F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:65.75

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ANY MATERIAL THAT REACTS WITH WATER.

Stability Condition to Avoid:PROTECT FROM FREEZING.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS.

Discla

imer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.