

TWIN DISC INC -- DISC, LINING, FRICTION MOLDED -- 3040-00-640-3744

=====
Product Identification
=====

Product ID:DISC, LINING, FRICTION MOLDED

MSDS Date:05/21/1993

FSC:3040

NIIN:00-640-3744

MSDS Number: BRPDV

=== Responsible Party ===

Company Name:TWIN DISC INC

Address:1328 RACINE STREET

City:RACINE

State:WI

ZIP:53403-1758

Country:US

Info Phone Num:414-634-1981

Emergency Phone Num:414-634-1981

Pre

parer's Name:DGSC-SSH

CAGE:61208

=== Contractor Identification ===

Company Name:TWIN DISC INC

Address:1328 RACINE STREET

Box:City:RACINE

State:WI

ZIP:53403-1758

Country:US

Phone:414-634-1981

CAGE:61208

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

=====
Hazards Identification
=====

Ro

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO
Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES
Health Hazards Acute and Chronic: ACUTE: MINOR EYES/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL DISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.

Explanation of Carcinogenicity: CONTAINS

A [1332-21-4] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure: INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.
DIARRHEA, VOMITING, AND NAUSEA.

Medical Conditions Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DILUTE WITH WATER. DO NOT INDUCE VOMITING. SEE DOCTOR.

===== Fire Fighting Measures =====

Flash Point: NONFLAMMABLE

Extinguishing Media: NONFLAMMABLE. USE WATER FOG, CARBON DIOXIDE, FOAM,
OR DRY CHEMICAL AS REQUIRED FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

=====

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE
RE-ENTRY OF

F ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED

ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. ITEM ASSUMED TO CONTAIN ASBESTOS BASED ON AVAILABLE INFORMATION.

===== Physical/Chemical Properties =====

HCC:T6

Solubility

ity in Water:INSOLUBLE

Appearance and Odor:DRY, MOLDED

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.

PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.