

DEVOE COATINGS CO -- DEVFLEX 601 595A 27880 SOFT WHITE -- 8010-01-208-7777

=====  
Product Identification  
=====

Product ID:DEVFLEX 601 595A 27880 SOFT WHITE

MSDS Date:10/02/1990

FSC:8010

NIIN:01-208-7777

MSDS Number: BRPJY

=== Responsible Party ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

City:LOUISVILLE

State:KY

ZIP:40207

Country:US

Info Phone Num:502-897-9861

Emergency Phone Num:

800-424-9300 (CHEMTREC)

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION\_INGREDIENT

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES

Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INHAL:IRRITATION OF RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS. SKIN OR EYE CONTACT:PRIMARY IRRITATION. CHRONIC:PROLONGED OR REPEATED BREATHING OF SPRAY MIST &/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

Explanation of Carcinogenicity:ANTIMONY TRIOXIDE:GROUP 2B(IARC).

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Agg

avated by Exposure:NONE WHEN USED I/A/W SAFE HANDLING & USE INFORMATION.

=====  
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. EYES:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CALL MD FOR MEDICAL TREATMENT. SKIN:REMOVE W/SOAP & WATER. REMOVE SOILED CLOTHING. INGEST:DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CALL MD IMMEDIATELY. TREAT SYMPTOMATICALLY.

=====  
===== F  
Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:1.1%

Extinguishing Media:IN CASE OF FIRE USE CO2, DRY CHEM, FOAM OR OTHER NPFA APPROVED METHOD FOR TREATING A CLASS B FIRE.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . SUMMON PROFESSIONAL FIREFIGHTERS. H2O SPRAY MAY BE INEFT. IF H2O IS USED, FOG NOZZ ARE PREF. IF(SUPDAT)

Unusual Fire/Explosion Hazard:DUE TO PRESS BUILD-UP, CLSD CNTNRS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURIN

G EMER CNDTNS, OVEREXP TO

DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPS MAY NOT BE(SUPDAT)

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WASH W/WATER. CONTAIN SPILLED MATERIAL & REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 110F & KEEP FROM FREEZ

ING.

KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELLED CONTAINERS. DO NOT GET IN EYES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:DO NOT BREATHE VAPS, SPRAY MIST/SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREAS W/UNRESTRICTED VENT & DURING SANDING/GRINDING OPERATIONS, USE NIOSH/MSHA APPRVD MECH

FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY (SUPDAT)

Ventilation:USE ONLY W/ADEQ VENT. PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC BELOW CURRENT(ING 11)

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:REMOVE & WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

Supplemental Safety and Health

FIRE F

IGHT PROC:EXPOSED TO FIRE/EXTREME HEAT, H\*2O SHOULD BE USED TO COOL CLSD CNTNRS & PVNT PRESS BUILD-UP/POSS AUTO-IGNIT. EXPLO HAZ:IMMED APPARENT. GET MD. HAZ DECOMP PROD:OF ANTIMONY. RESP PROT:& SANDING DUST. WHEN USED IN RESTRICTED VENT AREAS, WEAR NIOSH/MSHA APPRVD CHEM/MECH FILTERS DESIGNED TO REMOVE (ING 8)

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGS

Vapor Density:SEE INGS

Evaporation Rate &a

mp; Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:59.88

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY CAUSE HAZ FUMES WHEN HEATED TO DECOMP. FUMES MAY CONTAIN CO, CO\*2, NO\*X, CHLORINE, HCL, OXIDES & CHLORIDES (SUPDAT)

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.