

ALLIED CHEMICAL,ALLIED CORP -- GENETRON 12 DICHLORODIFLUOROMETHANE --
6830-00-106-1656

===== Product Identification =====

Product ID:GENETRON 12 DICHLORODIFLUOROMETHANE

MSDS Date:03/01/1982

FSC:6830

NIIN:00-106-1656

MSDS Number: BRTDP

=== Responsible Party ===

Company Name:ALLIED CHEMICAL,ALLIED CORP

Address:COLUMBIA RD AND PARK AVE

Box:1087R

City:MORRISTOWN

State:NJ

ZIP:07960

Country:US

Info Phon

e Num:201-455-3073

Emergency Phone Num:201-455-3073

CAGE:70308

=== Contractor Identification ===

Company Name:HONEYWELL INTL INC ENVIRONMENTAL SYSTEMS AND SERVICES

Address:101 COLUMBIA RD

Box:City:MORRISTOWN

State:NJ

ZIP:07962

Country:US

Phone:973-455-3922

CAGE:70308

===== Composition/Information on Ingredients =====

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:100

0 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN AND EYES: CONTACT WITH LIQUID CAN CAUSE FROST BITE, INDICATED BY PALLOR OR REDNESS, LOSS OF SENSATION AND SWELLING. INHALATION:ASPHYXIATION. THIS PRODUCT CAN CAUSE DEATH OR SERIOUS INJURY IF NOT HANDLED PROPERLY.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BT IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:FROST BITE, PALLOR, REDNESS, NUMBNESS, BREATHING DIFFICULTIES.
Medical Cond Aggravated by Exposure:NOT KNOWN.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION AND PROVIDE OXYGEN. CALL PHYSICIAN. DO NOT GIVE EPINEPHRINE. SKIN OR EYE CONTACT: IMMEDIATELY BATHE FROST BITE AREA WITH LUKEWARM WATER. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:NONFLAMMABLE. FOR SURROUNDING FIRE USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:LIQUID AND GAS UNDER PRESSURE. HEAT OF FIRE WILL PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. VENTILATE THE AREA AND ALLOW TO DISSIPATE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:HANDLE, TRANSPORT & STORE CAREFULLY/SECURELY TO AVOID ACCIDENTAL KNOCKING OVER/SEVERE

PHYSICAL IMPACTS. DO NOT EXPOSE TO DIRECT HEAT OR OVERPRESSURIZE
Other Precautions:DO NOT PUNCTURE OR DROP CYLINDERS OR EXPOSE TO
EXCESSIVE HEAT. USE AUTHORIZED CONTAINERS ONLY. CYLINDERS UNDER
PRESSURE, HANLE WITH GREAT CARE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED FOR NORMAL USE. FOR UNSUAL
SITUATIONS, WEAR SUPPLIED-AIR RESPIRATOR OR SELF-CONTAINED NIOSH
APPROVED BREATHING APPARATUS.

Ventilation:GENERAL

Protecti

ve Gloves:WEAR LEATHER GLOVES

Eye Protection:WEAR SAFETY GLASSES

Other Protective Equipment:SAFETY SHOES ARE RECOMMENDED WHEN HANDLING
CYLINDERS.

Work Hygienic Practices:FOLLOW OSHA REGULATIONS FOR HANDLING CYLINDERS.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-21F,-30C

Melt/Freeze Pt:M.P/F.P Text:-252F,-158C

Vapor Pres:70.3PSIG

Vapor Density:4.28 @ 0C

Spec Gravity:1.325@21C

.LIQUI

Evaporation Rate & Reference:N/R (GAS)

Solubility in Water:0.008

Appearance and Odor:COLORLESS LIQUIFIED GAS WITH FAINT ETHEREAL ODOR.

Percent Volatiles by Volume:GAS

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

POWDERED FORMS OF ALUMINUM, MAGNESIUM AND ZINC. ACTIVE METALS SUCH AS
SODIUM, POTASSIUM AND CALCIUM.

Stability Condition to Avoid:HIGH HEAT, TEMPERATURES ABOVE 550C,
LIGHTED CIGAETTES, HOT SPOTS, WELDI

NG.

Hazardous Decomposition Products:HALOGENS, HALOGEN ACIDS, AND POSSIBLY CARBONYL HALIDES, SUCH AS PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.