View NSN Online: https://aerobasegroup.com/nsn/6850-00-264-6571

ENGELHARD CORP., CHEMICAL CATALYSTS GROUP -- DESICCITE 25 -- 6850-00-264-6571

Product ID:DESICCITE 25 MSDS Date:05/19/1995 FSC:6850 NIIN:00-264-6571 MSDS Number: BRTFH === Responsible Party === Company Name: ENGELHARD CORP., CHEMICAL CATALYSTS GROUP Address:600 E. MCDOWELL ROAD City: JACKSON State:MS ZIP:39204 Country:US Info Phone Num:800-458-8650 **Emergency Phone** Num:800-458-8650/800-424-9300(CHEMTREC) CAGE:0NH81 === Contractor Identification === Company Name: ENGELHARD CORP Address:600 E. MCDOWELL ROAD Box:City:JACKSON State:MS ZIP:39204 Country:US Phone:800-458-6850 / 601-948-3966 CAGE:0NH81 Company Name: ENGELHARD CORP. Address:6801 COCHRAN DR Box:City:SOLON State:OH ZIP:44139 Country:US Phone:216-349-7300 CAGE:0FDV7 Company Name: INTERNATIONAL AEROSPACE TECHNOLOGIES, IN Box:UNKNOW CAGE:7U652

====== Composition/Information on Ingredients =====

=======

Ingred Name:BENTONITE (INCLUDES INGREDIENTS 2 AND 3.) CAS:1302-78-9 RTECS #:CT9450000 Fraction by Wt: SEE 2&3% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (DUST) ACGIH TLV:5 MG/M3 (DUST)

Ingred Name:SILICA, CRYSTALLINE - QUARTZ CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 1 - 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE TABLE Z-3 ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:ALUMINUM SILICATE, CAS:12141-46-7 Fraction by Wt: 97% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY TRACT. ACUTE- EYES:MAY CAUSE IRRITATION & DISCOMFORT. SKIN:MAY CAUSE IRRITATION, REDNESS. INHALE:CAUSES RESPIRATORY TRACT IRRITATION & MAY CAUSE DISABLING, PROGRES SIVE PULMONARY FIBROSIS (SI LICOSIS). ORAL:NO ADVERSE EFFECTS EXPECTED. CHRONIC- INHALATION MAY CAUSE LUNG DAMAGE. Explanation of Carcinogenicity:CONTAINS CRYSTALLINE SILICA (QUARTZ).

Explanation of Carcinogenicity:CONTAINS CRYSTALLINE SILICA (QUARTZ). Effects of Overexposure:IRRITATION, COUGH, DYSPNEA, WHEEZING, CHEST DISCOMFORT

Medical Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE EXISTING MEDICAL CONDITIONS SUCH AS RESPIRATORY AILMENTS.

First Aid:GET MEDICAL CARE IF SYMPTOMS PERSIST. EYES:IMM

EDIATELY FLUSH

WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:FLUSH WITH PLENTY OF WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED . SWALLOWED:IF LARGE QUANTITIES INGESTED, CONTACT PHYSICIAN. NOTE TO PHYSICAN:DESICCANT GENERATES HEAT AS IT ADSORBS WATER. USED PRODUCT CAN CONTAIN HAZARDOUS CHEMICALS.

Flash Point:NONE

Extinguishing Media:UNUSED MATERIAL WILL NOT BURN. USE WATER, CARBO N

DIOXIDE OR FOAM FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. USED MATERIAL MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. CAREFULLY SWEEP OR VACUUM THE SPILL AREA. COLLECT AND PLACE THE SPILLED MATERIAL IN A WASTE DISPOSAL CONTAINER. AVOID DUSTING. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN DRY PLACE, IN TIGHTLY CLOSED CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:WEAR GOGGLES IF DUST CAUSES EYE DISCOMFORT. WEAR A PROPERLY FITTED NIOSH-APPROVED DUST RESPIRATOR FOR DUSTY CONDITIONS. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. AVOID CONTACT WIT H E YES. OPEN CONTAINER SLOWLY.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF ENGINEERING CONTROLS ARE INADEQUATE TO CONTROL DUST CONCENTRATIONS TO AN ACCEPTABLE LEVEL, A NIOSH-APPROVED DUST RESPIRATOR SHOULD BE WORN IF NEEDED. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE IN STITUTED TO COMPLY WITH OSHA.

Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:COTTON/RUBBER/LATEX FOR REPEATE

D CONTACT Eye Protection: SAFETY GOGGLES FOR DUSTY CONDITIONS Other Protective Equipment: LONG SLEEVE WORK CLOTHING, EYE WASH FOUNTAIN Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING. VACUUM UP ANY DUST. LAUNDER CLOTHING BEFORE REUSE. Supplemental Safety and Health THE MANUFACTURER STATES THAT INDUSTRIAL HYGIENE SAMPLING HAS SHOWN THE **RESPIRABLE FRACTION OF CRYSTALLINE SILICA QUARTZ TO BE ONLY 0.1 -**0.115%. \_\_\_\_\_ HCC:N1 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN Spec Gravity:2.0 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference: NOT RELEVANT Solubility in Water:NEGLIGIBLE Appearance and Odor: GREY TO OFF-WHITE GRANULES; ODORLESS Stability Indicator/Materials to Avoid:YES STRONG ALKALI, STRONG OXIDIZING AGENTS Stability Condition to Avoid:MOISTURE Hazardous Decomposition Products:NONE == Waste Disposal Methods: DISCARD ANY PRODUCT (INCLUDING ANY RETAINED

MATERIALS OF USE), DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner wh

## atsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.