

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- RTV SILICONE COMPOUND --
6850-00-926-4913

===== Product Identification =====

Product ID:RTV SILICONE COMPOUND

MSDS Date:08/06/1990

FSC:6850

NIIN:00-926-4913

Kit Part:Y

MSDS Number: BSCXV

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone

Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLORTHOSILICATE

CAS:110990-60-2

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM

Ingred Name:IRON OXIDE (FE2O3)

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMET

HYL POLYSILOXANE SILANOL/ST

CAS:70131-67-8

Fraction by Wt: 60-80%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL RAT>40,000MG/KG(SILANOL)

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST:HARMFUL IF

SWALLOWED.SKIN:UNCURED PRODUCT MAY CAUSE IRRITATION.INHAL:MFR

STATES NO HAZARD KNOWN.EYES:MAY CAUSE IRRITATION

.CHRONIC-MAY CAUSE

RESPIRATORY,LIVER OR KIDNEY DAMAGE.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS

LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATING TO EYES AND SKIN.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF

RESPIRATORY OR SKIN DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH WATER FOR ATLEAST

15 MINUTES.GET

MEDICAL ATTENTION IF IRRITATION PERSISTS.INGEST:GET PROMPT QUALIFIED
MEDICAL ATTENTION.SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP
AND WATER.INHAL:REMOVE FROM EXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>400F,>204C

Autoignition Temp:Autoignition Temp Text:>500F

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL

PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.SENSITIVITY TO
STATIC DISCHARGE IS NOT EXPECTED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL &
PUT IN A CONTAINER FOR DISPOSAL. WASH AREA WITH DETERGENT & WATER
TO R

REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIPMENT.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT AND IGNITION SOURCES. KEEP
CONTAINERS CLOSED.

Other Precautions:AVOID EYE CONTACT!

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL CONDITIONS.

Ventilation:NORM

AL ROOM VENTILATION.

Protective Gloves:CLOTH

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYEWASH STATION

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>545F,>285C

Vapor Pres:NEGLIGIBLE

Spec Gravity:1.3

Evaporation Rate & Reference: