

FISKE BROS REFINING CO -- FISKE GG OIL -- 9150-01-048-9554

=====
Product Identification
=====

Product ID:FISKE GG OIL

MSDS Date:07/01/1990

FSC:9150

NIIN:01-048-9554

MSDS Number: BSCYM

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Preparer's Name:ROBER

T J.SIBILIA

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS "OIL MIST", WHICH IS NOT ENCOUNTERE

D IN NORMAL USAGE.)
CAS:8012-95-1
RTECS #:PY8030000
Other REC Limits:5MG/CUM,AS OIL MIST
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9293

Ingred Name:UNIDENTIFIED COMPONENTS
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: PROLONGED

CONTACT MAY CAUSE IRRITATION. INHALATION: VAPOR PRESSURE IS LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. INGESTION: PRODUCT HAS A LOW ORDER OF ORAL TOXICITY. HEALTH RISKS VARY FROM PERSON TO PERSON.AS A PRECAUTION, EXPOSURE TO LIQUIDS,VAPORS,MISTS,FUMES SHOULD BE MINIMIZED.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. INGESTION: PRODUCT HAS A LOW ORDER OF ORAL TOXICITY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. INHALATION: IF OVERCOME BY VAPOR FROM HOT PRODUCT, MOVE TO FRESH AIR. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

==
=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:275F,135C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANT. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WE

LD,
AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER LIQUID, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD INERT ABSORBENT. KEEP PRODUCT OUT OF SEWERS AND WATERCOURSES. NOTIFY AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATERCOURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:

STORE AND HANDLE IN COOL DRY AND WELL

VENTILATED AREA AWAY FROM HEAT, SPARKS, OPEN FLAME, AND STRONG OXIDANTS.

Other Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:LOCAL/GENERAL TO MAINTAIN ADEQUATE VENTILATION. USE LOCAL EXHAUST VENTILATION TO CAPTURE FUMES AND VAPORS AT SOURCE.

Protective Gloves:USE OIL RESISTANT GLOVES IF NEEDED.

Eye Protection:

IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Vapor Pres:5

Spec Gravity:0.81

Evaporation Rate & Reference: