View NSN Online: https://aerobasegroup.ae/nsn/6850-01-375-5555

## SENTRY CHEMICAL CO -- ELECTRON, DIELECTRIC SOLVENT, PART #0296 -- 6850-01-375-5555

Product ID:ELECTRON, DIELECTRIC SOLVENT, PART #0296

MSDS Date:03/31/1994

FSC:6850

NIIN:01-375-5555

MSDS Number: BSDVB === Responsible Party ===

Company Name: SENTRY CHEMICAL CO Address: 1481 ROCK MOUNTAIN BLVD

Box:748

City:STONE MOUNTAIN

State:GA ZIP:30083 Country:US

Info Phone Num:800-8 86-8240; 404-621-8240

Emergency Phone Num:800-877-3339; 404-934-4242

Preparer's Name: NONE

CAGE:8S927

=== Contractor Identification === Company Name: ECOLINK INC

Address:1481 ROCK MOUNTAIN BLVD

**Box:City:STONE MOUNTAIN** 

State:GA

ZIP:30083-1505 Country:US

Phone:800-886-8240/770-621-8240

CAGE:0WU71

Company Name: SENTRY CHEMICAL CO INC

Address:1481 ROCK MOUNTAIN BLVD

Box:748

City:STONE MOUNTAIN

State:GA ZIP:30086 Country:US

Phone:770-934-4242

CAGE:8S927

====== Composition/Information on Ingredi

Ingred Name: HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-47-8

Fraction by Wt: >80.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 MIST

ACGIH TLV:5 MG/M3 MIST 9394

Ingred Name: THE PRODUCT LISTED AS INGREDIENT #1 CONSISTS OF INGREDIENT #3 AND INGREDIENT #4 LISTED BELOW.

RTECS #:9999999ZZ

Other REC Limits: NONE RECOMMENDED

=========== Hazards Identification ===============

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 4.2 GMS/KG.

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: EXPOSURE TO HIGH CONCENTRATION OF VAPORS MAY CAUSE IRRITATION. SKIN: REPEATED EXPOSURE MAY CAUSE IRRITATION. INHALATION: EXCESSIVE INHALATION OF VAPORS MAY CAUSE DIZZINESS OR HEADACHE. IN GESTION: CAN CAUSE GASTROINTESTINAL IRRITATION. CHRONIC: LONG TERM SKIN CONTACT MAY CAUSE EXCESSIVE DRYING OR FLAKING.

Explanation of Carcinogenicity:NONE

Eff.

ects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DRYING, FLAKING. INHALATION: DIZZINESS, HEADACHE. ASPERATION INTO LUNGS MAY CAUSE INJURY. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA OR SHOWER USING

SOAP AND WATER. INHALATION: MOVE TO FRESH AIR. IF BREATHING DIFFICULT, GIV E OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBON. GET MEDICAL ATTENTION.

============ Fire Fighting Measures =========================

Flash Point Method:TCC Flash Point:147F,64C

Extinguishing Media: REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:TREAT AS A HYDROCARBON FIRE. WEAR SELF-CONTAINED, NIOSH APPROVED BREATHING APPARATU

S. Unusual Fire/Explosion Hazard:NON-TOXIC AND TOX COMBUSTION, STAY UPWIND OF FIRE.	XIC FUMES MAY FORM UPON
======================================	S ======
Spill Release Procedures:SMALL SPILL: REMOVE SO ABSORB LIQUID ON ABSORBENT MATERIAL. LA IGNITION. DIKE AREA OF SPILL. PUMP INTO STORY RUNOFFS TO SEWERS OR BOD IES OF WATER AUTHORITIES.  Neutralizing Agent:NONE SPE CIFIED BY MANUFACTURER.	ARGE SPILL: REMOVE SOURCES OF ORAGE TANK/DRUM. PREVENT
======================================	=======================================
Handling and Storage Precautions:TREAT AS A COM CONTAINER CLOSED. USE WITH ADEQUATE VECONTACT WITH FUMES OR LIQUID.  Other Precautions:AS WITH ANY COMBUSTIBLE OIL IN CONJUNCTION WITH THIS PRODUCT MUST FOR CONTAINER AFTER USE TO AVOID THE POSSIE COMBUSTION.	ENTILATON. AVOID EXCESSIVE  OR SOLVENT, ALL RAGS USED BE PLACED IN A METAL SEALABLE
===== Exposure Controls/Personal Protection =======	
Respiratory Protection:NOT REQUIRED UNDER CONVAPOR MIST IS GENERATED, USE NIOSH/MSHARESPIRATOR WITH A DUST AND MIST FILTER.  Ventilation:USE LOCAL EXHAUST/HOOD OR FAN VProtective Gloves:NITRILE GLOVES ARE RECOMMED Eye Protection:SAFETY GOGGLES ARE RECOMMED Other Protective Equipment:NONE REQUIRED.  Work Hygienic Practices:WASH AFTER HANDLING A	A APPROVED ORGANIC VAPOR ENTILATION. ENDED. NDED.
DRINKING, OR SMOKING. LAUNDER CONTAMINA Supplemental Safety and Health THIS PRODUCT CONTAINS HIGHLY REFINED ALIF	

THIS PRODUCT CONTAINS HIGHLY REFINED ALIPHATIC HYDROCARBONS AND TERPENES, WHICH ARE NOT CONSIDERED HAZARDOUS OR RESTRICTED BY EPA RCRA. ELECTRON, IN ITS PURCHASED FORM, IS NOT REGULATED UNDER SARA TIT LE III SECTIONS 311 & 312. ELECTRON DIELECTRIC IS COMBUSTIBLE AND SHOULD BE HANDLED WITH CARE AROUND OPEN FLAME.

======== Physical/Chemical Properties ==========

HCC:V4
Boiling Pt:B.P. Text:370F,188C
Vapor Pres:1
Spec Gravity:0.784
Evaporation Rate & Evaporation Rate