

ELDORADO CHEMICAL CO., INC -- ED-366 -- 6850-01-045-7931

=====
===== Product Identification =====

Product ID:ED-366
MSDS Date:11/18/1988
FSC:6850
NIIN:01-045-7931
MSDS Number: BSFRH
=== Responsible Party ===
Company Name:ELDORADO CHEMICAL CO., INC
Address:14350-LOOKOUT ROAD
Box:34837
City:SAN ANTONIO
State:TX
ZIP:78265
Country:US
Info Phone Num:512-653-9323
Emergency Phone Num:800-531-1088
Preparer's Name:
Name:PAT E. SMITH
CAGE:55208

==== Contractor Identification ====

Company Name:ELDORADO CHEMICAL COMPANY, INC.
Address:14350 LOOKOUT ROAD
Box:34837
City:SAN ANTONIO
State:TX
ZIP:78265-4837
Country:US
Phone:800-531-1088/ 210-653-2060
CAGE:55208

=====
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM MID-DISTILLATE (DIESEL MARINE FUEL)
CAS:68476-34-6
Fraction by Wt: 25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

In

gred Name:2-BUTOXYETHANOL (SARA III)
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9394

Ingred Name:ETHANOLAMINE
CAS:141-43-5
RTECS #:KJ5775000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3 PPM
ACGIH TLV:3 PPM/6 STEL; 9394

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT: BURNS EYES IMMEDIATELY.
SKIN: IRRITATION OF SKIN. DERMATITIS MAY OCCUR. INHALATION:
IRRITATION, DIZZINESS, NAUSEA, FATIGUE. CHRONIC: DERMATITIS MAY
OCCUR WITH SKIN CONTACT.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:SKIN & EYE IRRITATION. DERMATITIS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES; CONSULT PHYSICIAN.
SKIN: REMOVE CLOTHING, WASH WITH SOAP AND WATER. INHALATION: REMOVE
TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:TREATAS CLASS B (OIL TYPE) FIRE.
Fire Fighting Procedures:SAME AS FOR PETROLEUM NAPHTHA
Unusual Fire/Explosion Hazard:COMBUSTION MAY PRODUCE

NITROGEN OXIDES;
SELF-CONTAINED BREATHING APPARATUS MAY BE REQUIRED.

===== Accidental Release Measures =====

Spill Release Procedures:RINSE WITH WATER. AVOID PROLONGED SKIN CONTACT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:VAPOR HAZARD, COMBUSTIBLE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS REQUIRED IF LIMITS EXCEEDED.

Ventilation:100 FT/MIN

Protective Gloves:RUBBER

Eye Protection:FACE SHIELD OR GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:AVOID PROLONGED SKIN CONTACT.

Supplemental Safety and Health

MANUFACTURER SHOW ON MSDS AS NONE FOR FLASH POINT FOR THIS ITEM. THE ITEM CONTAINS 25% AS ALIPHATIC PETROLEUM NAPHTHAS. HAZARD IS SHOWN ON MSDS AS VAPOR HAZARD, COMBUSTIBLE.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:220F,104C

Melt/Freeze Pt:M.P/F.P Text: