

MILITEC INC -- MILITEC-1 -- 6850-01-378-3058

===== Product Identification =====

Product ID:MILITEC-1

MSDS Date:10/19/1992

FSC:6850

NIIN:01-378-3058

MSDS Number: BSGLL

=== Responsible Party ===

Company Name:MILITEC INC

Address:1911 N FORT MEYER DR SUITE #701

City:ARLINGTON

State:VA

ZIP:22209

Country:US

Info Phone Num:703-528-8371

Emergency Phone Num:703-528-8371

CAGE:EO190

=== Contractor Identification ===

Company Name:MILITEC INC

Address:11828 PIKA DR

Box:City:WALDORF

State:MD

ZIP:20602

Country:US

Phone:301-893-3910

CAGE:0KXE0

Company Name:MILITEC INC

Address:1911 N FORT MEYER DR #701

Box:City:ARLINGTON

State:VA

ZIP:22209

Country:US

Phone:703-528-8371

CAGE:EO190

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/CUM (OIL MIST)

ACGIH TLV:5 MG/CUM (OIL MIST)

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TYPICAL OF THAT FOR HYDROCARBON LUBRICANTS. ACUTE: INHALATION MAY CAUSE MILD RESPIRATORY IRRITATION TRACT. CONTACT WITH EYES MAY CAUSE IRRITATION. ASPIRATION OF PRODUCT DURING INGESTION OR VOMITING MA Y CAUSE CHEMICAL PNUEMOCONIOSIS. CHRONIC: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION OR DERMATITIS.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALATION: COUGHING, SHORTNESS OF BREATH. EYES: BURNING SENSATION, REDDENING, TEARING. SKIN: REDDNENING, DEFATTING, BURNING SENSATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
HMIS: SKIN AND RESPIRATORY DISORDERS

=====
First Aid Meas
ures
=====

First Aid:INHALED: REMOVE TO FRESH AIR. RESTORE BREATHING IF NEEDED. GET MEDICAL ATTENTION IF SYMPTOMS PERSISTS. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. SEE DOCTOR IF IRRITATION PERSISTS. SKIN: WASH WITH WATER. SEE DOCTOR IF IRRITATION PERSISTS.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:410F,210C
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS, WATER FOG
Fire Fighting Procedures:USE STANDARD PRECAUTIONS FOR OIL FIRE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:KEEP OUT OF WATERWAYS AND SEWERS. CONTAIN SPILL. ABSORB WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

=====

Handling and Storage Precautions:KEEP AWAY FROM OPEN FLAME. STORE IN ORIGINAL CONTAINER. KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:KEEP OFF OF FOODSTUFFS. AVOID EYE CONTACT. AVOID REPEATED OR PROLONGED SKIN CONTACT. AVOID BREATHING OIL MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL MIST OR SCBA, AS REQUIRED.

USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE IN WELL-VENTILATED AREA; IF NOT- USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST.

Protective Gloves:NITRILE IF SPILLED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NO SPECIAL EQUIPMENT REQUIRED.

Work Hygienic Practices:AVOID EYE CONTACT AND PROLONGED SKIN CONTACT. WASH THOROUGHLY AFTER USE. AVOID BREATHING OIL MIST.

Supplemental Safety and Health

NO PCB'S DETECTED AT OR ABOVE 2 PPM. MSDS INPUT PRIOR TO PROCUREMENT,

FOR EVALUATION PURPOSES BY THE SERVICES. USE: NEW & USED GASOLINE & DIESEL ENGINES, GEARBOXES, PUMPS, TRANSMISSIONS, COMPRESSORS, WEAPONS, 2 CYCLE ENGINES, FARM EQUIPMENT, INDUSTRIAL MACHINERY AND EQUIPMENT.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:528F,276C

Melt/Freeze Pt:M.P/F.P Text:-45F,-43C

Vapor Pres: