

DOW CORNING CORP -- MOLYKOTE 44 GREASE,MIL-L-15719A -- 9150-01-080-9652

=====
Product Identification
=====

Product ID:MOLYKOTE 44 GREASE,MIL-L-15719A

MSDS Date:03/07/1990

FSC:9150

NIIN:01-080-9652

MSDS Number: BSHMN

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-59

00

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:GENERAL DYNAMICS CORP

Address:BEING REPLACED BY FC #81755//////////

Box:City:FORT WORTH

State:TX

Country:US

CAGE

:2G999

=====
Composition/Information on Ingredients
=====

Ingred Name:LITHIUM SOAP THICHENER/LITHIUM STEARATE
CAS:4485-12-5
RTECS #:WI4370000
Fraction by Wt: 19%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,6-CIS-DIPHENYLHEXAMETHYLCYCLOTETRASILOXANE
CAS:33204-76-1
RTECS #:GZ4390000
Fraction by Wt: 0.04%
Other REC Limits:TWA 20 MCG/M3 DOW

Ingred Name:PHENYLHEPTAMETHYLCYCLOTETRASILOXANE
CAS:10448-09-6
RTECS #:GZ4392000
Fraction by Wt: 250F,>121C
Extinguishing Media:USE WAT
ER FOG, CARBON DIOXIDE, FOAM, SAND/EARTH OR
DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO
TAKE CARE OF ANY OIL-LIKE RESIDUES.
Neutralizing Agent:NOT RELEV
ANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN DRY PLACE AWAY FROM
OXIDIZERS.
Other Precautions:TRACES OF BENZENE, FORMALDEHYDE AND OTHER THERMAL
DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 302F(150C).
PROVIDE VENTILATION WHEN HANDLING PRODUCTS AT ELEVATED TEMPERATUES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE SHOULD BE NEEDED.
Ventilation:MECHANICAL

(GENERAL) RECOMMENDED.

Protective Gloves:WASHING AFTER HANDLING/AT MEALTIME

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME
NSN.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Decomp Temp:Decomp Text:302F,
150C

Vapor Pres: