

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL GRAY -- 8010-01-336-0526

===== Product Identification =====

Product ID:EXTERIOR TRIM ENAMEL GRAY

MSDS Date:03/23/1992

FSC:8010

NIIN:01-336-0526

MSDS Number: BSHYJ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-

941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L

RTECS #:9999999VO

Other REC Limits:NONE SPEC

IFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN
CONFINED AREAS LEAD TO MUCUS MEMBRANE IRRITATION, DIZZINESS,
HEADACHES. SKIN: IRRITATION OF SKIN. EYE: IRRITATION OF EYES.
INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSUMER & INDUSTRIAL
HANDLING AREN'T LIKELY CAUSE INJURY, HOW
EVER, INGESTION LARGER AMTS
COULD CAUSE SERIOUS INJURY.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS
DEVELOP. SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY
WITH PLENTY OF WATER, THEN SOAP & WATER. EYES: FLUSH IMMEDIATELY
WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR A
T LEAST
15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF
SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG OR WATER
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH &
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND
APPROPRIATELY LABELED.
Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING
VAPOR A

ND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IS MAINTAINED BELOW APPLICABLE LIMITS.

Protective

Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD

Other Protective Equipment:EYE WASH - SAFETY SHOWERS - GOGGLES - SAFETY GLASSES - IMPERVIOUS GLOVES.

Work Hygienic Practices:KEEP WORK AREA CLEAN. ALWAYS WASH HANDS THOROUGHLY WITH SOAP & WATER BEFORE HANDLING FOOD, DRINKS OR SMOKING.

Supplemental Safety and Health

REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Tex

t:212F,100C

Vapor Pres:23.8

Vapor Density:> AIR

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OR TINT

Percent Volatiles by Volume:7.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS

Hazardous Decomposition Prod

ucts:CARBON MONOXIDE AND CARBON DIOXIDE

Conditions to Avoid Polymerization:ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States o
f America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.