View NSN Online: https://aerobasegroup.com/nsn/8040-00-865-8991

Product ID:PSI-690 PRIMER MSDS Date:08/26/1993 FSC:8040 NIIN:00-865-8991 Kit Part:Y **MSDS Number: BSRZN** === Responsible Party === Company Name: POLYMERIC SYSTEMS, INC. Address:723 WHEATLAND STREET City:PHOENIXVILLE State:PA ZIP:19460 Country:US Info Phone Num:215-935-1170 Emergency Phone Num:215-935-117 0 Preparer's Name:ED CLUFF CAGE:0KND3 === Contractor Identification === Company Name: POLYMERIC SYSTEMS, INC. Address:723 WHEATLAND STREET Box:City:PHOENIXVILLE State:PA ZIP:19460 Country:US Phone:610-935-1170 CAGE:0KND3

Ingred Name:METHYL ISOBUTYL CARBINOL CAS:108-11-2 RTECS #:SA7350000 Fraction by Wt: 94% Other REC Limits:NONE SPECIFIED OSHA PEL:25 PPM ACGIH TLV:25 PPM

Ingred Name:ETHYL POLYSILICATE CAS:68412-37-3 Fraction

by Wt: 5% Other REC Limits:NONE SPECIFIED
Ingred Name:BUTYL POLYTITANATE CAS:9022-96-2 Fraction by Wt: 1% Other REC Limits:NONE SPECIFIED
Ingred Name:VOC: 6.5 LBS/GAL; 780 GRAMS/LITER RTECS #:9999999VO Other REC Limits:NONE SPECIFIED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: IRRITATION AND ANESTHESIA. CHRONIC: NONE
Effects of Overexposure:IRRITATION OF EYES, SKIN AND UPPER RESPIRATORY TRACT. Medical Cond Aggravated by Exposure:EYE, SKIN AND RESPIRATORY DISORDERS
MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.
======================================
First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT. INGESTION: WASH OUT MOUTH WITH WATER. CALL A PHYSICIAN.
======================================
Flash Point Method:TCC Flash Point:103F,39C Lower Limits:1 Upper Limits:5.5
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL POWDER, ALCOHOL FOAM Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. Unusual Fire/Explosion Hazard:VAPOR MAY TRAVEL CONSIDERABLE DISTANCE TO IGNITION SOURCES AND FLASH BACK.

========= Accidental Release Me

asures =================

Spill Release Procedures: TAKE UP WITH ABSORBENT MATERIAL. STORE IN APPROPRIATE CONTAINER. AVOID PROLONGED INHALATION OF VAPOR OR CONTACT WITH LIQUID. WASH RESIDUES WITH LARGE AMOUNTS OF WATER. Neutralizing Agent: WATER.

Handling and Storage Precautions:AVOID IGNITION SOURCES: FLAME, SPARKS, EXTREME HEAT. Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED.

HCC:F4 Boiling Pt:B.P. Text:270F,132C Melt/Freeze Pt:M.P/F.P Text:-130F,-90C Vapor Pres:3.7 @ 20C Vapor Density:3.5 Spec Gravity:0.80 (WATER=1) pH:7 Viscosity:2 CPS @ 25C Evaporation Rate & amp; Reference:>1 Solubility in Water:98% Appearance and Odor:COLORLESS LIQUID; PLEASANT, SWEET ODOR Percent Volatiles by Volume:96

======

Stability Indicator/Materials to Avoid:YES ACID CHLORIDES AND OXIDIZING AGENTS Stability Condition to Avoid:OPEN FLAMES, SPARKS AND EXTREME HEAT Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SILICA AND TITANIA FROM COMBUSTION

Waste Disposal Methods: INCINERATE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.