

DEL PAINT CORP -- TT-E-2784, ENAMEL, YELLOW 13538 -- 8010-01-334-0910

===== Product Identification =====

Product ID:TT-E-2784, ENAMEL, YELLOW 13538

MSDS Date:02/10/1993

FSC:8010

NIIN:01-334-0910

MSDS Number: BSSNY

=== Responsible Party ===

Company Name:DEL PAINT CORP

Address:3105 EAST RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-424-9300

CHEMTREC

Preparer's Name:ONEY FLEMING

CAGE:EO523

=== Contractor Identification ===

Company Name:DEL PAINT CORP

Address:3105 E RENO AVE

City:OKLAHOMA CITY

State:OK

ZIP:73117-6699

Country:US

Phone:405-672-1431/800-866-6823

CAGE:EO523

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:EKTASOLVE EEH SOLVENT

CAS:1559-35-9

RTECS #:KK96250

00
Fraction by Wt: 3.32%
Other REC Limits:NONE SPECIFIED

Ingred Name:BENZYL ALCOHOL
CAS:100-51-6
RTECS #:DN3150000
Fraction by Wt: 3.32%
Other REC Limits:NONE SPECIFIED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOE
CAS:108-01-0
RTECS #:KK6125000
Fraction by Wt: 0.38%
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 0.827 LBS/GAL; 99.24 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Sk
in:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY
PASSAGES.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION OF VAPOR OR MIST CAN CAUSE
HEADACHES, NAUSEA, IRRITATION OF NOSE, THROAT & LUNGS. EYE CONTACT:
SLIGHT IRRITATION. SKIN CONTACT PROLONGED OR REPEATED CAN CAUSE
SLIGHT IRRITATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISEASE MAY BE
AGGRAVAT
ED BY EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION: MOVE SUBJECT TO FRESH AIR. EYE CONTACT: FLUSH
WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, CONSULT PHYSICIAN IF
IRRITATION PERSISTS. SKIN CONTACT: WASH AFFECTED AREA THOROUGHLY
WITH SOAP & WATER. INGESTION: IF SWALLOWED, GIVE 2 GLASSES OF
WATER TO DRINK, CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash P

oint:NO FLASH

Lower Limits:NONE

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS
(PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL
PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 100C/212F.
POLYMER FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY,
USE CARE

TO AVOID FALLING. CONTAIN SPILLS WITH INERT MATERIAL
(SAND, EARTH). TRANSFER LIQUID AND SOLID DIKING MATERIAL TO
SEPARATE SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.

Other Precautions:DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICA

L FILTER RESPIRATOR TO REMOVE

SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION.

Ventilation:NORMAL, SUCH AS A FAN

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:EYE WASH STATION

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:> AIR

Spec Gravity:

1.01 (WATER=1)
pH:9 MAX
Viscosity:77 TO 95 KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:YELLOW LIQUID WITH SLIGHT ODOR
Percent Volatiles by Volume:60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
THERE ARE NO KNOWN MATERIALS WHICH ARE INCOMPATIBLE WITH THIS PRODUCT.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD
ACRYLIC MONOMERS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP SPILLS AND CLEANING RUN OFF OUT OF
MUNICIPAL SEWERS AND BODIES OF WATER. CONSULT FEDERAL, STATE, OR
LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH
AND ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.