

ARCOS ALLOYS DIV OF HOSKINS MFG. CO. -- BARE WIRE FILLER METALS (STAINLESS STEEL 310 INDICATED) -- 3439-00-880-1652

=====
Product Identification
=====

Product ID:BARE WIRE FILLER METALS (STAINLESS STEEL 310 INDICATED)

MSDS Date:04/01/1991

FSC:3439

NIIN:00-880-1652

MSDS Number: BTHVS

=== Responsible Party ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG. CO.

Address:#1 ARCOS DRIVE

Box:308

City:MOUN

T CARMEL

State:PA

ZIP:17851

Country:US

Info Phone Num:717-339-5200

Emergency Phone Num:717-339-5200, CHEMTREC 800-424-9300

CAGE:03805

=== Contractor Identification ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG CO

Address:#1 ARCOS DRIVE

Box:308

City:MTCARMEL

State:PA

ZIP:17851

Country:US

Phone:717-339-5200, CHEMTREC 800-424-9300

CAGE:03805

=====
Composition/Information on Ingredients
=====

Ingred Name:CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by

Wt: 28%
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 2.5%
OSHA PEL:C 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 22.5%
Other REC Limits:1 MG/CUM
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: BALANCE

=====
Hazards Identification
=====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:**TARGET-ORGANS:RESPIRATORY SYSTEM**
PRODUCT POSES NO HEALTH HAZARD AS SHIPPED, BUT MAY POSE A HEALTH HAZARD DURING USE. ELECTRIC ARC WELDING RAYS CAN INJURE EYES & BURN SKIN. DUST, FUMES & GASES CAN BE DANGEROUS TO YOUR HEALTH. LUNG DAMAGE MAY RESULT FROM OVEREXPOSURE. CHRONIC EXPOSURE MAY RESULT IN NEUROLOGICAL
Explanation of Carcinogenicity:CHROMIUM & NICKEL ARE LISTED AS POSSIBLE CARCINOGENS BY IARC, NTP & OSHA. SEE INDIVIDUAL REPORTS FOR DETAILS.
Effects of Overexposure:SHORT TERM EXPOSURE TO WELDING FUMES, GASES OR DUST MAY RESULT IN DIZZINESS, NAUSEA, FEVER, DRYNESS, WATERY EYES, HEADACHE, BREATHING DIFFICULTY, FREQUENT COUGHING, CHEST PAINS, & EVEN PULMONARY EDEMA , ASPHYXIATION, & DEATH.
Medical Cond Aggra

vated by Exposure:SOME WORKERS MAY EXPERIENCE DISCOMFORT AT CONCENTRATIONS BELOW THE THRESHOLD LIMIT VALUES & OTHERS MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS.

=====
First Aid Measures
=====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL.
INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION. SKIN:WASH AFFECTED AREA WITH SOAP & WATER. EYES:FLUSH WITH LARGE AMOUNTS OF FRESH WATER FOR AT LEAST 15 MINS. INGESTION:GET IMMEDIATE MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:NON-FLAMMABLE
Extinguishing Media:MFR GAVE NO INFORMATION OF MSDS.
Fire Fighting Procedures:MFR GAVE NO INFORMATION OF MSDS.
Unusual Fire/Explosion Hazard:NONFLAMMABLE; HOWEVER, ARCS, SPARKS & MOLTEN METALS CAN IGNITE FLAMMABLES & COMBUSTIBLES OR CAUSE EXPLOSION.

=====
Accidental Release Measures
=====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES & PLACE IN DOT APPROVED CONTAINERS. AVOID INHALATION & SKIN EXPOSURE
Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS.

=====
Handling and Storage
=====

Handling and Storage Precautions:MFR GAVE NO INFORMATION OF MSDS.
Other Precautions:MFR GAVE NO INFORMATION OF MSDS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED WELD FUME RESPIRATOR OR AIR-SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN CONFINED SPACES OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS.

Ventilation:USE ENOUGH VENTILATION TO KEEP DUST, FUMES, GASES FROM WORKERS BREATHING ZONE & GENERAL AREA. KEEP EXPOSURE BELOW PEL/TLV.

Protective Gloves:WEAR GLOVES

Eye Protection:OSHA APPROVED GOGGLES, GLASSES, FACE SHIELD

Other Protective Equipment:WEAR FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING/WELD.

Work Hygienic Practices:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS.
Supplemental Safety and Health

*MONITOR AIR QUALITY AT WORKERS BREATHING ZONE (INSIDE HELMET) TO DETERMINE IF RESPIRATOR IS REQUIRED. **SELECT WELDING LENS FROM AMERICAN WELDING SOCIETY F2.2. ***REFER TO ANSI Z49.1 AND OSHA 29CFR19 10 FOR FURTHER INFORMATION.

===

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Appearance and Odor:BARE FILLER METALS ARE SOLID WIRE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MFR GAVE NO INFORMATION OF MSDS.

Stability Condition to Avoid:MFR GAVE NO INFORMATION OF MSDS.

Hazardous Decomposition Products:WELDING & HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION & QUANTITY VARIES.

C

Conditions to Avoid Polymerization:MFR GAVE NO INFORMATION OF MSDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and dis

claims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.