

EXIDE CORP -- LEAD-ACID BATTERY -- 6140-01-203-4694

===== Product Identification =====

Product ID:LEAD-ACID BATTERY

MSDS Date:09/01/1993

FSC:6140

NIIN:01-203-4694

MSDS Number: BTRKY

=== Responsible Party ===

Company Name:EXIDE CORP

Address:645 PENN ST

City:READING

State:PA

ZIP:19612-4205

Country:US

Info Phone Num:215-378-0798

Emergency Phone Num:215-378-0798

CAGE:20038

=== Contractor Identificatio

n ===

Company Name:CAMPBELL, J R EQUIPMENT CO

Address:3659 PARKWAY LN

Box:City:HILLIARD

State:OH

ZIP:43026-1236

Country:US

Phone:614-876-0132

CAGE:7T245

Company Name:CHICAGO INDUSTRIAL TRADING CO

Address:1901 LANDMEIER RD

Box:City:ELK GROVE VILLAGE

State:IL

ZIP:60007

Country:US

Phone:708-981-0090

CAGE:0K4U5

Company Name:EXIDE CORP

Address:645 PENN STREET

Box:14205

City:READING

State:PA

ZIP:19612-4205

Country:US

Phone:610-378-0500/0798

CAGE:20038

Company Name:EXIDE CORP.-GENERAL BATTERY CORP

Addr

ess:645 PENN STREET  
Box:City:READING  
State:PA  
ZIP:19601  
Country:US  
Phone:215-378-0527/800-424-9300(CHEMTREC)  
CAGE:08163  
Company Name:FIATALLIS N. AMERICA INC/CENTRAL PARTS OPERATION  
Address:245 E NORTH AVE  
Box:City:WHEATON  
State:IL  
ZIP:60187  
Country:US  
CAGE:2L857

=====  
===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 53% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M  
3;DUST 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)  
CAS:7440-36-0  
RTECS #:CC4025000  
Fraction by Wt: 0.2% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.5 MG/M3  
ACGIH TLV:0.5 MG SB/M3; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)  
CAS:7440-38-2  
RTECS #:CG0525000  
Fraction by Wt: 0.003% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.5 MG/M3 (AS)  
ACGIH TLV:0.01,A1 MG/M3; 9394  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM, METAL  
CAS

:7440-70-2  
RTECS #:EV8040000  
Fraction by Wt: 0.02% %  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TIN  
CAS:7440-31-5  
RTECS #:XP7320000  
Fraction by Wt: 0.06% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3; 9293

Ingred Name:POLYPROPYLENE RUBBER  
CAS:9003-07-0  
Fraction by Wt: 5-6% %  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SULFURIC ACID (SARA III)  
CAS:7664-93-9  
RTECS #:WS5600000  
Fraction by Wt: 30-40% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 M  
G/M3; 9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - FUSED  
CAS:60676-86-0  
RTECS #:VV7328000  
Fraction by Wt: 3-5% %  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3 RDUST; Z-3  
ACGIH TLV:0.1 MG/M3 RDUST;9394

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:HAZARDOUS EXPOSURE TO LEAD COMPOUNDS

CAN OCCUR ONLY WHEN PRODUCT IS HEATED, OXIDIZED OR OTHERWISE PROCESSED OR DAMAGED TO CREATE DUST, VAPOR OR FUME. INHALATION OF LEAD DUST MAY CAUSE RESPIRATORY TRACT IRRITATION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES. MAY CAUSE EYE IRRITATION.

Explanation of Carcinogenicity:CONTAINS INORGANIC ARSENIC [7440-38-2] AND LEAD WHICH ARE LISTED BY NTP AND IARC AND REGULATED BY OSHA AS CARCINOGENS.

Effects of Overexposure:ACUTE: HEADACHE, FATIGUE, ABDOMINAL PAIN, LOSS

OF APPETITE, MUSCULAR ACHES AND WEAKNESS, SLEEP DISTURBANCES AND IRRITABILITY. CHRONIC: ANEMIA, NEUROPATHY--PARTICULARLY OF THE MOTOR NERVES WITH WRIST D ROP, KIDNEY DAMAGE, REPRODUCTIVE CHANGESIN BOTH MALES AND FEMALES.

Medical Cond Aggravated by Exposure:LEAD AND ITS COMPOUNDS CAN AGGRAVATE SOME FORMS OF KIDNEY, LIVER AND NEUROLOGIC DISEASES.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. GARGLE, WASH NOSE AND LIPS.

CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN IMMEDIATELY. SKIN: WASH IMMEDIATELY WITH SOAP AND WATER. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. CONSULT PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Lower Limits:4.1 % (H2)

Upper Limits:74.2% (H2)

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USE POSITIVE PRESSURE, SELF-CONTAINED

BREATHING APPARATUS. WATER APPLIED TO ELECTRO

LYTE GENERATES HEAT &

CAUSES IT TO SPLATTER. WEAR CAID-RESISTANT CLOTHING.

Unusual Fire/Explosion Hazard:HIGHLY FLAMMABLE HYDROGEN GAS (H2) IS

GENERATED DURING CHARGING AND OPERATION. TO AVOID RISK, KEEP IGNITION SOURCES AWAY FROM BATTERIES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW OF MATERIALM, CONTAIN/ABSORB SPILLS

WITH DRY SAND, EARTH, VERMICULITE. DO NOT USE COMBUSTIBLE

MATERIALS. IF POSSIBLE, CAREFULLY NEUTR

ALIZE ELECTROLYTE WITH SODA

ASH, SODIUM BICARBONATE, LIME , ETC. WEAR ACID-RESISTANT CLOTHING,  
BOOTS, GLOVES

Neutralizing Agent:SODA ASH, SODIUM BICARBONATE, LIME.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE BATTERIES IN COOL, DRY, WELL-  
VENTILATED AREAS WITH IMPERVIOUS SURFACES AND ADEQUATE CONTAINMENT  
IN THE EVENT OF SPILLS.

Other Precautions:BATTERIES SHOULD BE STORED UNDER ROOF FOR PROTECTION  
AGAINST ADVERS  
E WEATHER CONDITIONS. SEPARATE FROM INCOMPATIBLE  
MATERIALS. STORE AND HANDLE ONLY IN AREAS WITH ADEQUATE WATER  
SUPPLY AND SPILL CONTR OL. AVOID DAMAGE TO CONTAINERS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL CONDITIONS. WHEN  
CONCENTRATIONS OF SULFURIC ACID MIST ARE KNOWN TO EXCEED PEL, USE  
NIOSH OR MSHA-APPROVED RESPIRATORY PROTECTION.

Ventilation:STORE AND HANDLE IN WELL-VENTILATED AREA. IF MECHANICAL  
VENTILATION IS USED, COMPONENTS MUST BE ACID RESISTANT.

Protective Gloves:RUBBER OR PLASTIC ACID-RESISTANT

Eye Protection:CHEMICAL GOGGLES/FACE SHIELD

Other Protective Equipment:ACID RESISTANT APRON. UNDER SEVERE EXPOSURE  
OR EMERGENCY, WEAR ACID-RESISTANT CLOTHING AND BOOTS.

Work Hygienic Practices:HANDLE BATTERIES CAUTIOUSLY TO AVOID SPILLS.  
MAKE CERTAIN VENT CAPS ARE ON SECURELY. AVOID CONTACT WITH INTERNAL  
PARTS.

Supplemental Safety and Health

IN AREAS WHERE SULFURIC ACID IS H  
ANDLED IN CONCENTRATIONS GREATER THAN

1%, EMERGENCY EYEWASH STATIONS AND SHOWERS SHOULD BE PROVIDED, WITH  
UNLIMITED WATER SUPPLY.

=====  
===== Physical/Chemical Properties =====

HCC:Z4

Boiling Pt:B.P. Text:203-240F

Vapor Pres:17 TO 11

Vapor Density:>1

Spec Gravity:1.23 TO 1.350

Evaporation Rate & Reference:LESS THAN 1

Solubility in Water:100%

Appearance and Odor:MANUFACTURED ARTICLE; NO APPARENT ODOR. ELECTROLYTE  
IS CLEAR LIQUID.

=====  
===== Stabili

ty and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS, BASES, HALIDES, HALOGENATES, POTASSIUM NITRATE,  
PERMANGANATE, PEROXIDES, REDUCING AGENTS, NASCENT HYDROGEN

Stability Condition to Avoid: PROLONGED OVERCHARGE, SOURCES OF IGNITION.

Hazardous Decomposition Products: TOXIC METAL FUME/VAPOR/DUST; CONTACT  
WITH STRONG ACID IN PRESENCE OF NASCENT HYDROGEN MAY GENERATE  
ARSINE GAS.

===== Disposal Considerations =====

==

Waste Disposal Methods: SEND SPENT BATTERIES TO SECONDARY LEAD SMELTER  
FOR RECYCLING. PLACE NEUTRALIZED SLURRY INTO SEALED CONTAINERS AND  
DISPOSE OF AS HAZARDOUS WASTE AS APPLICABLE. WASTE SHOULD BE  
MANAGED IN ACCORDANCE WITH APPROVED LOCAL, STATE AND FEDERAL  
REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.