

STEVENS INDUSTRIES -- X-948H EPOXY ADHESIVE, HARDENER -- 8040-00-753-4800

=====
Product Identification
=====

Product ID:X-948H EPOXY ADHESIVE, HARDENER

MSDS Date:05/10/1991

FSC:8040

NIIN:00-753-4800

Kit Part:Y

MSDS Number: BTSQK

=== Responsible Party ===

Company Name:STEVENS INDUSTRIES

Address:39 AVE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Info Phone Num:201-437-6500 FAX:201-473-0366

E

Emergency Phone Num:201-333-6986(CHEMTREC 800-424-9300)

Preparer's Name:CHARLES FRIEDMAN

CAGE:70372

=== Contractor Identification ===

Company Name:STEVENS INDUSTRIES

Address:39 AVE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Phone:201-437-6500

CAGE:70372

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 60-80%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGI

H TLV:10 MG/M3 TDUST; 9394

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9394

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 200F,>93C

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: WEAR
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTETCIVE GEAR.

Un

usual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY
BE BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID PERSONAL CONTACT. SCOOP INTO CLOSABLE
CONTAINERS & DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT GET IN EYES, ON SKIN OR
CLOTHES. STORE IN TIGHTLY CLOSED CONTAINERS IN A DRY AREA. WASH
THOROUGHLY AFTER HANDLING.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR EMERGENCY
OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR
CARTRIDGE OR SCBA, AS REQUIRED. USE RESPIRATORY PROTECTION IAW
MANUFACTURER'S RECOMMENDATIONS & 29 CFR 1910.134.

Ventilation:LOCAL EXHAUST RE

COMMENDED, GENERAL EXHAUST AS A MINIMUM TO
MAINTIAN EXPOSURE BELOW TLV/PEL.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING. LAUNDER
CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>200F,>93C

Spec Gravity:1.87

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK GREY, PLEASANT ODOR

Percent Volatiles by Volume:NEGLBL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS.

Stability Condition to Avoid:AVOID EXPOSURE TO STRONG OXIDIZING AGENTS
AND STRONG MINERAL ACIDS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE,
ALDEHYDES, NITROGEN OXIDES.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional adv

ice to verify and
assume responsibility for the suitability of this information to their
particular situation.