

EASTMAN KODAK COMPANY -- 847 1484 EKTACOLOR RA BLEACH FIX & REPLENISHER, PART B --
6750-01-319-5407

===== Product Identification =====

Product ID:847 1484 EKTACOLOR RA BLEACH FIX & REPLENISHER, PART B

MSDS Date:10/17/1997

FSC:6750

NIIN:01-319-5407

MSDS Number: BTTCN

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

In

fo Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition

/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 70-75%
Other REC Limits:NONE RECOMMENDED

Ingred Name:FERRIC AMMONIUM ETHYLENEDIAMINETETRAACETIC ACID
CAS:21265-50-9
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (CERCLA)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE LOW HAZ FOR
RECOMMENDED HNDLG.EYES:NO SPECIFIC HAZ KNOWN.MAY CAUSE TRANSIENT
IRRIT.SKIN:LOW HAZ FOR RECOMMENDED HNDLG.INGEST:EXPECTED TO BE LOW
INGESTION HAZ.
Explanation of Carcinogenicity:PER MSDS:CARCINOGENIC
ITY
CLASSIFICATION:IARC/ACGIH/NTP/OSHA:NONE.
Effects of Overexposure:TRANSIENT EYE IRRIT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL:IF SYMPTOMATIC MOVE TO FRESH AIR.TREAT
SYMPTOMATICALLY.GET MED ATTN IF SYMPTOMS PERSIST.EYES:ANY MATL THAT
CONTACTS EYE SHOLD BE WASHED OUT IMMED W/WATER.SYMPTOMS OCCUR GET
MED ATTN.SKIN:WASH W/ SOAP & WATER.GET MED ATTN IF SYMPTOMS
OC

CUR.INGEST:DRINK 1-2 GLASSES OF WATER.SEEK MED ATTN.NEVER GIVE ANYTHING BY MOUTH TO UNCONSC PERSON.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire

/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:FLUSH TO SEWER W/LG AMTS OF WATER.OTHERWISE ABSORB W/VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID PROL/REP BREATH MIST/VAP.AVOID

CONTACT W/EYES,PORL/REP CONTACT W/SKIN.USE W/ADEQU VENTI.KEEP FRM CONTACT W/OXIDIZING MATLS.KEEP CNTNR TIGHT CLSD

Other Precautions:KEEP AWAY FRM INCOMPA SUBST.PROPERTIES:LOW BIOCHEM OXY DEMAND,LITTLE POT TO CAUSE OXY DEPLETION IN AQU SYS,LOW POT TO AFFECT AQU ORGANISMS,LOW POT TO AFFECT 2ND WASTE TREAT MICROB METAB,MOD POT TO AFF ECG GERM/EARLY GROWTH OF SOME (SUPPLEME)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protectio

n:NONE SHOULD BE NEEDED.FULL-FACE

POSITIVE-PRESSURE AIR-SUPPL RESP MUST BE WORN IF HAZ DECOMPO PRODS LIKELY TO BE RELEASED OR HAVE BEEN RELEASED.SEE STABILITY/REACTIVITY SEC.RESP USED INSTITUTE PROGRAM TO ASSURE COMPLIANCE W/29CFR1910.134.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)

SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, GOGGLES.

Other Protecti

ve Equipment:EYEBATH, WASHING FACILITIES.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.GOOD INDUSTRIAL HYGIENE PRACTICE TO MIN SKIN/EYE CONTACT.

Supplemental Safety and Health

OTHER PRECAUT:PLANTS,LOW POT TO AFFECT GROWTH OF SOME PLANT SEEDLINGS,LOW POT TO BIOCONCEN.DIL W/LG AMT OF H2O/2ND WASTE TREAT MATL NOT EXPECTED TO CAUSE ADVERSE ENVIRO EFFECTS. THIS NSN ONLY FOR PART B;PNIND:W WORK SOLN;SEE NSN 6750-01-319-4154 FOR PART A.TO MAKE 25 GALLONS.

=====

=== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.10

pH:5.6

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID, REDDISH-BROWN COLOR, SLIGHT AMMONIA ODOR

Percent Volatiles by Volume:70-75

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/M

aterials to Avoid:YES

STRONG OXIDIZING AGENTS, BASES, SODIUM HYPOCHLORITE(BLEACH).

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HAZ COMBUST PROD:CO,CO2,OXIDES OF NITROGEN.HAZ DECOMPO PROD:AMMONIA,CHLORAMINE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO NATIONAL/STATE/LOCAL LAWS.FLUSH TO SEWER W/LG AMTS OF WATER.CHEM SUBJ TO REPORTING REQMTS O

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.