

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL, ALKYD, GLOSS, LO VOC CN  
BLUE 15044, ID 774504 -- 8010-00-298-2302

=====  
Product Identification  
=====

Product ID:ENAMEL, ALKYD, GLOSS, LO VOC CN BLUE 15044, ID 774504

MSDS Date:01/25/1994

FSC:8010

NIIN:00-298-2302

MSDS Number: BTZYP

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)  
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF735000

0

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)  
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE (SOLVENT)

RTECS #:MP3850000  
Fraction by Wt: 5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM; 240 MG/M3  
ACGIH TLV:50 PPM; 240 MG/M3

Ingred Name:SILICA, CRYSTALLINE (PIGMENT)  
CAS:14808-60-7  
RTECS #:VV7330000

Fraction by Wt: 115F) AND SOURCES  
OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISP  
OSE IN ACCORDANCE WITH FEDERAL, STATE, &  
LOCAL LAWS OR REGULATIONS. THIS PRODUCT, IF DISCARDED DIRECTLY,  
WOULD BE CLASSIFIED A HAZARDOUS WASTE BASED ON ITS IGNITABILITY  
CHARACTERISTIC (FLASH POINT 140F OR LESS). PROPER RCRA  
CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, war  
rants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.