

J T BAKER INC -- ALUMINUM NITRATE, 9-HYDRATE, 0528 -- 6810-00-300-5168

=====
Product Identification
=====

Product ID:ALUMINUM NITRATE, 9-HYDRATE, 0528

MSDS Date:05/01/1989

FSC:6810

NIIN:00-300-5168

MSDS Number: BTZYW

=== Responsible Party ===

Company Name:J T BAKER INC

Address:222 RED SCHOOL LANE

City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Info Phone Num:800-582-2537

Emergency Phone Num:908-85

9-2151;800-424-9300(CHEMTREC)

CAGE:DO803

=== Contractor Identification ===

Company Name:J T BAKER INC

Address:222 RED SCHOOL LANE

City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:1-800-582-2537

CAGE:DO803

Company Name:MALLINCKRODT BAKER, INC.

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:800-582-2537

CAGE:70829

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (III) NITRATE, NONAHYDRATE (1:3:9); (ALUMINUM

NITRATE, 9-HYDRATE)
CAS:7784-27-2
RTECS #:BD1050000
Fraction by Wt: 98-100%
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT) 264 MG/KG.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:INHAL:IRRITATION OF UPPER
RESPIRATORY TRACT. SKIN/EYE CONTACT:IRRITATION. SKIN
ABSORPTION:NONE IDENTIFIED. INGEST:NAUSEA,
VOMITING. CHRONIC:NONE
IDENTIFIED.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE IDENTIFIED.

===== First Aid Measures =====

First Aid:INGEST:CALL MD. IF SWALLOWED, IF CONSCIOUS, IMMEDIATELY
INDUCE VOMITING. INHAL:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE
ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.
SKIN:FLUSH W/ WATER. EYES:IMMEDIATELY F
LUSH W/PLENTY OF WATER FOR
AT LEAST 15 MINUTES.

===== Fire Fighting Measures =====

Flash Point Method:CC
Extinguishing Media:USE WATER SPRAY.
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP .
MOVE CNTNRS FROM FIRE AREA IF IT CAN BE DONE W/OUT RISK. USE WATER
TO KEEP FIRE-EXPOSED CNTNRS COOL.
Unusual Fire/Explosion Hazard:STRONG OXIDIZER. CONT W/COMBUST MATLS,
FLAMM MATLS/POWDERED METALS CAN CAUSE FIRE/EXPLO. CAN REACT

VIOLENTLY W/SHOCK, FRICTION OR HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROT
CLTHG. KEEP COMBUSTIBLES (WOOD, PAPER, OIL, ETC) AWAY FROM SPILLED
MATL. WITH CLEAN SHOVEL, CAREFULLY PLACE MATL INTO CLEAN, DRY CNTNR
& COVER; REMOVE FROM AR EA. FLUSH SPILL AREA W/WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Hand

ling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE
SEPARATELY & AWAY FROM FLAMMABLE & COMBUSTIBLE MATERIALS.

Other Precautions:CAUSES IRRITATION. HARMFUL IF SWALLOWED. STRONG
OXIDIZER. CONTACT W/COMBUST MATLS, FLAMM MATLS OR POWDERED METALS
CAN CAUSE FIRE/EXPLO. AVOID CONT W/EYES, SKIN, CLTHG. AVOID BRTHG
DUST. USE W/ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENT
CONDITIONS

EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A NIOSH/MSHA APPROVED
DUST/MIST RESPIRATOR IS RECOMMENDED. IF CONCENTRATION EXCEEDS
CAPACITY OF RESPIRATOR, A NIOSH/MSHA APPRVD SCBA IS ADVISED.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV
REQUIREMENTS. VENT HOOD.

Protective Gloves:BUTYL RUBBER GLOVES.

Eye Protection:SAFETY GOGGLES.

Other Protective Equipment:UNIFORM IS RECOMMENDED. LAB COAT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supp

lemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:163F,73C

Solubility in Water:APPRECIABLE (>10%)

Appearance and Odor:WHITE CRYSTALLINE SOLID; ODORLESS.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MOST COMMON METALS, STRONG REDUCING AGENTS, COMBUSTIBLE MATERIALS,
ORGANIC MATERIALS, CYANID

ES.

Stability Condition to Avoid:MOISTURE.

Hazardous Decomposition Products:OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W ALL APPLICABLE FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER: D001 (IGNITABLE WASTE).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.