

DYNATRON/BONDO CORP -- 6294 DENT FILLER, COMPONENT B -- 8030-00-926-2135

=====
Product Identification
=====

Product ID:6294 DENT FILLER, COMPONENT B

MSDS Date:04/12/1994

FSC:8030

NIIN:00-926-2135

Kit Part:Y

MSDS Number: BVBHC

=== Responsible Party ===

Company Name:DYNATRON/BONDO CORP

Address:2160 HILLS AVE

City:ATLANTA

State:GA

ZIP:30318-2217

Country:US

Info Phone Num:404-696-2730

Emergency Phone

Num:404-696-2730/800-241-3386

Preparer's Name:M WHEELLOCK

CAGE:16522

=== Contractor Identification ===

Company Name:BONDO/MAR-HYDE CORP

Address:3700 ATLANTA INDUSTRIAL PKWY NW

Box:City:ATLANTA

State:GA

ZIP:30331

Country:US

Phone:404-696-2730

CAGE:16522

=====
Composition/Information on Ingredients
=====

Ingred Name:DIBENZOYL PEROXIDE (SARA III)

CAS:94-36-0

RTECS #:DM8575000

Fraction by Wt: 50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3--10 HR SHIFT

ACGIH TLV:5 MG/M3--1

0 HR SHIFT

=====
===== Hazards Identification =====
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE IRRITATION, MINOR SKIN IRRITATION. CHRONIC: NONE KNOWN.

Effects of Overexposure:EYES: MAY CAUSE EYE IRRITATION. SKIN: PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION AND REDNESS. INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT, AND LUNG. INGESTION: MAY CAUSE TOXIC EFFECTS.

Medical Cond Aggravated b

y Exposure:NO INFORMATION FOUND

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES & CONTACT A PHYSICIAN. SKIN: WASH IMMEDIATELY WITH SOAP & WATER. CONSULT A PHYSICIAN IF DISCOMFORT DEVELOPS. INHALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN IF DISCOMFORT PERSISTS. INGESTION: ADMINISTER LARGE QUANTITIES OF WATER IF PERSON IS CONSCIOUS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

IMMEDIATELY CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:SCC

Flash Point:>200F,>93C

Extinguishing Media:WATER FOG OR SPRAY, CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:EVACUATE AREA AND APPLY WATER FROM A SAFE DISTANCE.

Unusual Fire/Explosion Hazard:PEROXIDES AND DECOMPOSITION PRODUCTS ARE FLAMMABLE AND CAN IGNITE WITH EXPLOSIVE FORCE IF CONFINED.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:AVOID CONTACT WITH SKIN. MATERIAL LEFT UNCOVERED COULD INCREASE FIRE HAZARD DUE TO EVAPORATION OF WATER & LEACHING OF PLASTICIZER AWAY FROM BENZOYL PEROXIDE. DIKE TO PREVENT RUNOFF FROM ENTERING DRAIN S, SEWERS, STREAMS, ETC. TRANSFER INTO CONTAINER.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:KEEP AWAY FROM ALL SOURCES OF HEAT AND IGNITION SUCH AS RADIATORS, STEAM PIPES AND DIRECT SUNLIGHT

T. DO NOT

STORE NEAR COMBUSTIBLES.

Other Precautions:DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. DO NOT BREATHE VAPORS. KEEP CONTAINERS CLOSED. KEEP FROM FREEZING. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED IF TLVS ARE EXCEEDED

Ventilation:MECHANICAL

Protective Gloves:NEOPRENE OR POLYVINYL ALCOHOL

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD

Other Protective Equ

ipment:EYE WASH STATION SHOULD BE AVAILABLE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Decomp Temp:Decomp Text:200F,93C

Spec Gravity:1.2+/- 0.15@77F

Viscosity:250,000 CPS

Solubility in Water: